

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22004 + SLK290	
光源	LLD2411LCB1 ×1	500.0 lm
管理番号	K0193688 (0) DB1	
BZ分類	BZ1 / 0.9 / BZ2 / 2.3 / BZ3 / 8.5 / BZ4	

器具効率	92%	天井	80%				70%				50%				30%				0%									
	上方光束 9%		下方光束 83%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%							
室指数	照明率 (X0.01)																				ZCM							
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6							
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6							
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56							
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56							
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	65	57	52	49	64	57	52	48	61	55	51	48	59	54	50	47	45
	等価発光面積	c m ²		1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	82	76	71	68	80	74	70	67	76	72	68	65	73	69	66	63	60
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	87	83	79	76	85	81	78	75	81	78	75	73	77	75	72	70	66			
	横方向 (A)	縦方向 (B)	3.0	4.0	5.0	7.0	10.0	89	85	82	79	87	83	80	78	83	80	77	75	79	77	74	73	68				
H m	0.82 H m	0.86 H m	4.0	5.0	7.0	10.0	91	88	85	82	89	86	83	81	85	82	80	78	81	79	77	76	71					
			5.0	7.0	10.0	92	89	87	85	90	88	85	83	86	84	82	80	82	80	80	79	77	73					
			7.0	10.0	94	92	90	88	91	90	88	86	87	86	84	83	83	82	81	80	80	75						
			10.0	95	93	92	90	93	91	90	89	88	87	86	85	84	84	83	82	82	77							

