

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22004 + SLK290	
光源	LLD2421LCB1 ×1 500.0 1m	
管理番号	K0193692 (0) DB1	
BZ分類	BZ1/1.1 / BZ2/3.5 / BZ3	

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 9 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	84 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	等価発光面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	81	83	87	89	90	92	93	95	96
		c m ²		1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	83	87	89	90	92	93	95	96		
取付高さ	器具間隔最大限		H m		0.48 H m	0.51 H m	4.0	5.0	7.0	10.0	92	93	95	96							

