

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22004 + SLK290	
光源	LLD2401LCB1 ×1 500.0 lm	
管理番号	K0192484 (1) DR1	
BZ分類	BZ1	

器具効率	39 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	39 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	3.2	2.9	2.8	2.7	3.2	2.9	2.8	2.7	3.1	2.9	2.8	2.7	3.1	2.9	2.7	2.7	2.6		
		0.8	3.4	3.2	3.1	3.0	3.4	3.2	3.1	3.0	3.4	3.2	3.1	3.0	3.3	3.1	3.0	2.9	2.9		
		1.0	3.6	3.4	3.3	3.2	3.6	3.4	3.3	3.2	3.5	3.4	3.2	3.2	3.4	3.3	3.2	3.1	3.1		
		1.25	3.7	3.6	3.4	3.3	3.7	3.5	3.4	3.3	3.6	3.5	3.4	3.3	3.6	3.4	3.4	3.3	3.2		
下方投影面積	c m ²	1.5	3.8	3.7	3.5	3.5	3.8	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.5	3.4	3.3		
		2.0	3.9	3.8	3.7	3.6	3.9	3.8	3.7	3.6	3.8	3.7	3.6	3.6	3.7	3.6	3.6	3.5	3.5		
取付高さ	器具間隔最大限		2.5	4.0	3.9	3.8	3.7	3.9	3.8	3.8	3.7	3.8	3.8	3.7	3.6	3.8	3.7	3.7	3.6		
	横方向 (A)	縦方向 (B)	3.0	4.0	3.9	3.8	3.8	4.0	3.9	3.8	3.8	3.9	3.8	3.8	3.7	3.8	3.8	3.7	3.6		
H m	0.87 H m	0.86 H m	4.0	4.1	4.0	3.9	3.9	4.0	3.9	3.9	3.8	3.9	3.9	3.8	3.8	3.9	3.8	3.8	3.7		
			5.0	4.1	4.0	4.0	3.9	4.0	4.0	3.9	3.9	4.0	3.9	3.9	3.8	3.9	3.8	3.8	3.8	3.7	
			7.0	4.1	4.1	4.0	4.0	4.1	4.0	4.0	4.0	4.0	4.0	3.9	3.9	3.9	3.9	3.8	3.7		
			10.0	4.1	4.1	4.1	4.1	4.1	4.1	4.0	4.0	4.0	4.0	4.0	4.0	3.9	3.9	3.9	3.8		

