

# 屋内照明器具特性

|         |   |  |
|---------|---|--|
| 品番 (品名) | SLB15785 + SLK22006 + SLK290                  |  |
| 光源      | LLD2421LCB1 ×1                      500.0 l m |  |
| 管理番号    | K0193692 (0) DB 1                             |  |
| BZ分類    | BZ1 / 1.1 / BZ2 / 3.5 / BZ3                   |  |

|        |                  |          |      |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
|--------|------------------|----------|------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率   | 93 %             | 天井       | 80 % |      |    |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|        | 上方光束<br>9 %      |          | 反射率  | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |
| 下方光束   | 84 %             | 床        |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
| 室指数    | 照明率 ( X 0.01 )   |          |      |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     | ZCM |
| 保守率    | 良 0.63           | 0.6      | 0.6  | 66   | 58 | 53 | 50   | 65   | 58 | 53 | 50   | 63   | 56 | 52 | 49   | 60   | 55 | 51 | 49  | 47  |
|        | 中 0.6            | 0.6      | 0.8  | 73   | 65 | 60 | 57   | 71   | 65 | 60 | 56   | 68   | 63 | 59 | 56   | 66   | 61 | 58 | 55  | 53  |
|        | 否 0.56           | 0.6      | 1.0  | 77   | 70 | 65 | 62   | 75   | 69 | 65 | 61   | 72   | 67 | 63 | 60   | 69   | 65 | 62 | 59  | 57  |
| 下方投影面積 | c m <sup>2</sup> | 1.25     | 81   | 75   | 70 | 66 | 79   | 73   | 69 | 66 | 76   | 71   | 67 | 64 | 73   | 69   | 66 | 63 | 60  |     |
|        |                  | 1.5      | 83   | 78   | 73 | 70 | 81   | 76   | 72 | 69 | 78   | 74   | 70 | 68 | 75   | 71   | 69 | 66 | 63  |     |
| 等価発光面積 | c m <sup>2</sup> | 2.0      | 87   | 82   | 78 | 75 | 85   | 80   | 77 | 74 | 81   | 78   | 75 | 72 | 78   | 75   | 72 | 70 | 67  |     |
|        |                  | 2.5      | 89   | 85   | 81 | 78 | 87   | 83   | 80 | 77 | 83   | 80   | 77 | 75 | 80   | 77   | 75 | 73 | 70  |     |
| 取付高さ   | 器具間隔最大限          |          | 3.0  | 90   | 87 | 83 | 81   | 88   | 85 | 82 | 80   | 84   | 82 | 79 | 77   | 81   | 79 | 77 | 75  | 71  |
| H m    | 横方向 (A)          | 縦方向 (B)  | 4.0  | 92   | 89 | 87 | 84   | 90   | 87 | 85 | 83   | 86   | 84 | 82 | 80   | 83   | 81 | 79 | 78  | 74  |
|        | 0.48 H m         | 0.51 H m | 5.0  | 93   | 91 | 88 | 86   | 91   | 89 | 87 | 85   | 87   | 86 | 84 | 82   | 84   | 82 | 81 | 80  | 75  |
|        |                  |          | 7.0  | 95   | 93 | 91 | 89   | 93   | 91 | 89 | 88   | 89   | 87 | 86 | 85   | 85   | 84 | 83 | 82  | 77  |
|        |                  |          | 10.0 | 96   | 94 | 93 | 91   | 94   | 92 | 91 | 90   | 90   | 89 | 88 | 87   | 86   | 85 | 84 | 84  | 79  |

