

# 屋内照明器具特性

|         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | SLB15785+SLK22007+SLK290                     |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LLD2411LCB1 ×1                      500.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0193247 (3) DB1                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ1/0.9/BZ2/2.8/BZ3                          |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |              |    |      |    |      |    |      |    |      |    |      |    |      |    |      |     |     |     |
|--------|------------------|---------|--------------|----|------|----|------|----|------|----|------|----|------|----|------|----|------|-----|-----|-----|
| 器具効率   | 87 %             | 天井      | 80 %         |    |      |    | 70 % |    |      |    | 50 % |    |      |    | 30 % |    |      |     | 0 % |     |
|        |                  |         | 壁            | 70 | 50   | 30 | 10   | 70 | 50   | 30 | 10   | 70 | 50   | 30 | 10   | 70 | 50   | 30  | 10  | 0 % |
|        |                  |         |              | 床  | 10 % |    |      |    | 10 % |    |      |    | 10 % |    |      |    | 10 % |     |     |     |
| 上方光束   | 14 %             | 室指数     | 照明率 ( X0.01) |    |      |    |      |    |      |    |      |    |      |    |      |    |      | ZCM |     |     |
| 下方光束   | 73 %             |         |              |    |      |    |      |    |      |    |      |    |      |    |      |    |      |     |     |     |
| 保守率    | 良<br>中<br>否      | 0.63    | 0.6          | 59 | 51   | 46 | 43   | 57 | 50   | 46 | 42   | 54 | 48   | 44 | 42   | 52 | 47   | 43  | 41  | 38  |
|        |                  | 0.6     | 0.8          | 65 | 58   | 53 | 50   | 64 | 57   | 52 | 49   | 60 | 55   | 51 | 48   | 57 | 52   | 49  | 46  | 44  |
|        |                  | 0.56    | 1.0          | 70 | 63   | 58 | 54   | 68 | 61   | 57 | 54   | 64 | 59   | 55 | 52   | 60 | 56   | 53  | 50  | 47  |
|        |                  |         | 1.25         | 73 | 67   | 63 | 59   | 71 | 66   | 61 | 58   | 67 | 62   | 59 | 56   | 63 | 60   | 57  | 54  | 51  |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 76           | 70 | 66   | 62 | 74   | 69 | 65   | 61 | 69   | 65 | 62   | 59 | 65   | 62 | 59   | 57  | 53  |     |
|        |                  | 2.0     | 79           | 75 | 71   | 68 | 77   | 73 | 69   | 66 | 72   | 69 | 66   | 64 | 68   | 65 | 63   | 61  | 57  |     |
| 取付高さ   | 器具間隔最大限          |         | 2.5          | 81 | 77   | 74 | 71   | 79 | 75   | 72 | 69   | 74 | 71   | 69 | 67   | 70 | 68   | 66  | 64  | 59  |
|        | 横方向 (A)          | 縦方向 (B) | 3.0          | 83 | 79   | 76 | 74   | 80 | 77   | 74 | 72   | 76 | 73   | 71 | 69   | 71 | 69   | 67  | 66  | 61  |
| H m    | 0.77H m          | 0.77H m | 4.0          | 85 | 82   | 79 | 77   | 82 | 80   | 77 | 75   | 77 | 75   | 73 | 72   | 73 | 71   | 70  | 68  | 63  |
|        |                  |         | 5.0          | 86 | 84   | 81 | 79   | 83 | 81   | 79 | 77   | 79 | 77   | 75 | 74   | 74 | 73   | 71  | 70  | 64  |
|        |                  |         | 7.0          | 87 | 86   | 84 | 82   | 85 | 83   | 82 | 80   | 80 | 79   | 77 | 76   | 75 | 74   | 73  | 72  | 66  |
|        |                  |         | 10.0         | 88 | 87   | 86 | 85   | 86 | 85   | 83 | 82   | 81 | 80   | 79 | 78   | 76 | 75   | 75  | 74  | 68  |

