

屋内照明器具特性	
品番 (品名)	XL X4 3 0 WD WT
光源	LED4000_85_2960 x1 2960.0 lm
管理番号	K0132401 (2) DB 1
BZ分類	BZ6/0.7/BZ5/2.3/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	12%	床	10%				10%				10%				10%				0%			
下方光束	88%	室指数	照明率 (X0.01) ZCM																			
保守率	良	0.83	0.6	5.3	4.1	3.3	2.7	5.1	3.9	3.2	2.7	4.8	3.7	3.1	2.6	4.4	3.6	3.0	2.5	2.2		
	中	0.81	0.8	6.2	5.0	4.2	3.6	6.0	4.9	4.1	3.6	5.6	4.7	4.0	3.5	5.2	4.4	3.8	3.4	3.0		
	否	0.77	1.0	6.9	5.7	4.9	4.3	6.6	5.6	4.8	4.2	6.2	5.3	4.6	4.1	5.8	5.0	4.4	4.0	3.6		
			1.25	7.4	6.4	5.6	5.0	7.2	6.2	5.5	4.9	6.7	5.9	5.3	4.7	6.3	5.6	5.0	4.6	4.2		
下方投影面積		cm ²	1.5	7.9	6.9	6.1	5.5	7.6	6.7	6.0	5.4	7.1	6.3	5.7	5.2	6.6	6.0	5.5	5.1	4.6		
等価発光面積		cm ²	2.0	8.4	7.6	6.9	6.3	8.1	7.4	6.7	6.2	7.6	7.0	6.4	6.0	7.1	6.6	6.2	5.8	5.3		
取付高さ	器具間隔最大限		2.5	8.8	8.0	7.4	6.9	8.5	7.8	7.3	6.8	8.0	7.4	6.9	6.5	7.5	7.0	6.6	6.3	5.8		
	横方向 (A)	縦方向 (B)	3.0	9.0	8.4	7.8	7.3	8.8	8.2	7.6	7.2	8.2	7.7	7.3	6.9	7.7	7.3	7.0	6.6	6.1		
1.5m	1.94m	2.16m	4.0	9.4	8.8	8.4	7.9	9.1	8.6	8.2	7.8	8.6	8.2	7.8	7.5	8.1	7.7	7.4	7.1	6.6		
2	2.55	2.72	5.0	9.6	9.1	8.7	8.3	9.3	8.9	8.5	8.2	8.8	8.4	8.1	7.8	8.3	8.0	7.7	7.5	6.9		
2.5	3.17	3.3	7.0	9.8	9.5	9.1	8.8	9.6	9.2	8.9	8.7	9.0	8.8	8.5	8.3	8.6	8.3	8.1	7.9	7.4		
3	3.79	3.9	10.0	10.0	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.3	9.1	8.9	8.7	8.8	8.6	8.4	8.3	7.7		

