

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | SLB15785 + SLK22008 |           |
| 光源      | LLD2421LCB1 ×1      | 500.0 l m |
| 管理番号    | K0193000 (0) DB1    |           |
| BZ分類    | BZ1                 |           |

|        |                  |          |                  |          |          |     |      |      |     |     |      |      |    |    |      |      |    |    |     |     |    |    |    |
|--------|------------------|----------|------------------|----------|----------|-----|------|------|-----|-----|------|------|----|----|------|------|----|----|-----|-----|----|----|----|
| 器具効率   | 97 %             | 天井       | 80 %             |          |          |     | 70 % |      |     |     | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |    |    |    |
|        | 上方光束<br>0 %      |          | 壁                | 70       | 50       | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |    |    |    |
| 下方光束   | 97 %             | 床        |                  | 10 %     |          |     |      | 10 % |     |     |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |    |    |    |
| 室指数    | 照明率 ( X0.01 )    |          |                  |          |          |     |      |      |     |     |      |      |    |    |      |      |    |    |     | ZCM |    |    |    |
| 保守率    | 良 0.67           | 0.6      | 0.6              | 81       | 75       | 72  | 69   | 80   | 75  | 72  | 69   | 79   | 74 | 71 | 69   | 78   | 74 | 71 | 69  | 68  |    |    |    |
|        | 中 0.63           |          | 0.8              | 87       | 82       | 79  | 76   | 86   | 82  | 78  | 76   | 85   | 81 | 78 | 76   | 84   | 80 | 77 | 75  | 74  |    |    |    |
|        | 否 0.56           |          | 1.0              | 91       | 86       | 83  | 81   | 90   | 86  | 83  | 80   | 88   | 85 | 82 | 80   | 87   | 84 | 81 | 80  | 78  |    |    |    |
| 下方投影面積 | c m <sup>2</sup> | 等価発光面積   | c m <sup>2</sup> | 1.25     | 94       | 90  | 87   | 84   | 93  | 89  | 86   | 84   | 91 | 88 | 86   | 84   | 90 | 87 | 85  | 83  | 82 |    |    |
|        |                  |          |                  | 1.5      | 96       | 92  | 89   | 87   | 95  | 91  | 89   | 87   | 93 | 90 | 88   | 86   | 91 | 89 | 87  | 86  | 84 |    |    |
| 取付高さ   | 器具間隔最大限          |          | H m              | 0.41 H m | 0.41 H m | 2.5 | 99   | 97   | 95  | 93  | 98   | 96   | 94 | 93 | 96   | 95   | 93 | 92 | 95  | 93  | 92 | 91 | 89 |
|        | 横方向 (A)          | 縦方向 (B)  |                  |          |          | 3.0 | 100  | 98   | 97  | 95  | 99   | 97   | 96 | 94 | 97   | 96   | 94 | 93 | 95  | 94  | 93 | 92 | 90 |
| H m    | 0.41 H m         | 0.41 H m | 4.0              | 101      | 100      | 98  | 97   | 100  | 99  | 98  | 97   | 98   | 97 | 96 | 95   | 97   | 96 | 95 | 94  | 92  |    |    |    |
|        |                  |          | 5.0              | 102      | 101      | 100 | 99   | 101  | 100 | 99  | 98   | 99   | 98 | 97 | 96   | 97   | 96 | 96 | 95  | 93  |    |    |    |
| H m    | 0.41 H m         | 0.41 H m | 7.0              | 103      | 102      | 101 | 100  | 102  | 101 | 100 | 100  | 99   | 98 | 98 | 98   | 97   | 97 | 96 | 94  |     |    |    |    |
|        |                  |          | 10.0             | 103      | 103      | 102 | 102  | 102  | 102 | 101 | 101  | 100  | 99 | 99 | 98   | 98   | 98 | 98 | 97  | 95  |    |    |    |

