

# 屋内照明器具特性

品番 (品名)	SLB15785 + SLK22008 + SLK290	
光源	LLD2411LCB1 ×1                      500.0 lm	
管理番号	K0193061 (0) DB 1	
BZ分類	BZ4/0.7/BZ5/3.5/BZ6	

器具効率	89%	天井	80%				70%				50%				30%				0%												
	上方光束		26%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%										
	下方光束		63%		床	10%				10%				10%				10%				0%									
室指数	照明率 ( X0.01 )																				ZCM										
保守率	良	0.63	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	4.8	3.8	3.2	2.7	4.6	3.7	3.1	2.7	4.1	3.4	2.9	2.5	3.7	3.1	2.7	2.4	2.0
	中	0.6	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	5.5	4.6	3.9	3.4	5.3	4.4	3.8	3.3	4.7	4.0	3.5	3.1	4.3	3.7	3.2	2.9	2.5
	否	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	6.0	5.1	4.5	4.0	5.7	4.9	4.3	3.8	5.1	4.5	4.0	3.6	4.6	4.1	3.7	3.3	2.8
	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	6.5	5.6	5.0	4.5	6.2	5.4	4.8	4.3	5.5	4.9	4.4	4.0	5.0	4.5	4.1	3.7	3.2	
下方投影面積	c m <sup>2</sup>																														
	等価発光面積																														
取付高さ	器具間隔最大限																														
	横方向 (A)	縦方向 (B)																													
H m	0.60 H m	0.60 H m																													

