

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22011 + SLK290	
光源	LLD3421LCB1 ×1 700.0 lm	
管理番号	K0193245 (0) DB1	
BZ分類	BZ2 / 0.9 / BZ3 / 3.5 / BZ4	

器具効率	86%	天井	80%				70%				50%				30%				0%		
	上方光束		14%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		72%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	5.4	4.6	4.0	3.6	5.3	4.5	4.0	3.6	4.9	4.3	3.8	3.5	4.7	4.1	3.7	3.4	3.2
	中	0.6	0.6	0.8	6.1	5.3	4.8	4.4	5.9	5.2	4.7	4.3	5.6	5.0	4.5	4.2	5.2	4.7	4.4	4.1	3.8
	否	0.56	0.6	1.0	6.6	5.9	5.3	4.9	6.4	5.7	5.2	4.8	6.0	5.4	5.0	4.7	5.6	5.2	4.8	4.5	4.2
			0.56	1.25	7.0	6.3	5.8	5.4	6.8	6.2	5.7	5.3	6.4	5.9	5.5	5.1	6.0	5.6	5.2	5.0	4.6
下方投影面積	cm ²		1.5	7.3	6.7	6.2	5.8	7.1	6.5	6.1	5.7	6.6	6.2	5.8	5.5	6.2	5.9	5.5	5.3	4.9	
	等価発光面積		cm ²	2.0	7.7	7.2	6.7	6.4	7.4	7.0	6.6	6.3	7.0	6.6	6.3	6.0	6.5	6.2	6.0	5.8	5.3
取付高さ	器具間隔最大限		2.5	7.9	7.5	7.1	6.8	7.7	7.3	6.9	6.6	7.2	6.9	6.6	6.3	6.8	6.5	6.3	6.1	5.6	
	横方向 (A)	縦方向 (B)	3.0	8.1	7.7	7.3	7.1	7.8	7.5	7.2	6.9	7.3	7.1	6.8	6.6	6.9	6.7	6.5	6.3	5.8	
Hm	0.63Hm	0.63Hm	4.0	8.3	8.0	7.7	7.4	8.0	7.8	7.5	7.3	7.6	7.3	7.1	6.9	7.1	6.9	6.8	6.6	6.1	
			5.0	8.4	8.2	7.9	7.7	8.2	7.9	7.7	7.5	7.7	7.5	7.3	7.2	7.2	7.1	6.9	6.8	6.3	
			7.0	8.6	8.4	8.2	8.0	8.3	8.1	8.0	7.8	7.8	7.7	7.5	7.4	7.4	7.3	7.1	7.0	6.5	
			10.0	8.7	8.5	8.4	8.3	8.4	8.3	8.2	8.1	7.9	7.8	7.7	7.6	7.5	7.4	7.3	7.2	6.6	

