

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22012 + SLK290	
光源	LLD3401LCB1 ×1 700.0 lm	
管理番号	K0192481 (1) DR1	
BZ分類	BZ1	

器具効率	38 %	天井	80 %				70 %				50 %				30 %				0 %															
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %															
		床	10 %				10 %				10 %				10 %				0 %															
上方光束	0 %	室指数																照明率 (X0.01)																ZCM
下方光束	38 %																																	
保守率	良 中 否	0.67	0.6	31	29	27	26	31	29	27	26	30	28	27	26	30	28	27	26	26														
		0.63	0.8	34	32	30	29	34	32	30	29	33	31	30	29	32	31	30	29	28														
		0.56	1.0	35	34	32	31	35	33	32	31	34	33	32	31	34	33	32	31	30														
			1.25	37	35	34	33	36	35	34	33	36	34	33	32	35	34	33	32	32														
下方投影面積	c m ²	1.5	37	36	35	34	37	36	35	34	36	35	34	34	36	35	34	33	33															
		2.0	38	37	36	35	38	37	36	35	37	36	36	35	37	36	35	35	34															
取付高さ	器具間隔最大限		2.5	39	38	37	36	39	38	37	36	38	37	36	37	36	36	35	35															
	横方向 (A)	縦方向 (B)	3.0	39	38	38	37	39	38	37	37	38	38	37	36	37	37	36	35															
H m	0.87 H m	0.86 H m	4.0	40	39	39	38	39	39	38	38	39	38	38	37	38	37	37	36															
			5.0	40	40	39	39	40	39	39	38	39	38	38	38	38	38	38	37	36														
			7.0	40	40	40	39	40	40	39	39	39	39	39	39	38	38	38	37															
			10.0	41	40	40	40	40	40	40	40	39	39	39	39	39	38	38	37															

