

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22013	
光源	LLD3401LCB1 ×1	700.0 lm
管理番号	K0193963 (0) DB 1	
BZ分類	BZ1	

器具効率	77 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	77 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	5.5	4.9	4.4	4.1	5.5	4.8	4.4	4.1	5.3	4.8	4.4	4.1	5.2	4.7	4.4	4.1	4.0
	中	0.63	0.8	6.3	5.7	5.3	5.0	6.2	5.7	5.3	5.0	6.0	5.6	5.2	5.0	5.9	5.5	5.2	5.0	4.8
	否	0.56	1.0	6.7	6.2	5.8	5.6	6.6	6.2	5.8	5.6	6.5	6.1	5.8	5.5	6.3	6.0	5.7	5.5	5.4
			1.25	7.1	6.6	6.3	6.0	7.0	6.6	6.3	6.0	6.8	6.5	6.2	6.0	6.7	6.4	6.1	5.9	5.8
下方投影面積	cm ²		1.5	7.3	6.9	6.6	6.3	7.2	6.8	6.6	6.3	7.0	6.7	6.5	6.3	6.9	6.6	6.4	6.2	6.1
等価発光面積	cm ²		2.0	7.6	7.3	7.0	6.8	7.5	7.2	6.9	6.7	7.3	7.1	6.9	6.7	7.1	6.9	6.8	6.6	6.5
取付高さ	器具間隔最大限		2.5	7.7	7.5	7.2	7.1	7.6	7.4	7.2	7.0	7.5	7.3	7.1	6.9	7.3	7.1	7.0	6.9	6.7
	横方向 (A)	縦方向 (B)	3.0	7.8	7.6	7.4	7.2	7.7	7.5	7.4	7.2	7.6	7.4	7.2	7.1	7.4	7.3	7.1	7.0	6.9
Hm	1.32Hm	1.32Hm	4.0	8.0	7.8	7.6	7.5	7.9	7.7	7.6	7.4	7.7	7.6	7.5	7.3	7.5	7.4	7.3	7.2	7.1
			5.0	8.0	7.9	7.8	7.7	8.0	7.8	7.7	7.6	7.8	7.7	7.6	7.5	7.6	7.5	7.4	7.4	7.2
			7.0	8.1	8.0	7.9	7.8	8.0	7.9	7.9	7.8	7.9	7.8	7.7	7.6	7.7	7.6	7.6	7.5	7.3
			10.0	8.2	8.1	8.1	8.0	8.1	8.0	8.0	7.9	7.9	7.9	7.8	7.8	7.8	7.7	7.7	7.6	7.4

