

# 屋内照明器具特性

品番 (品名)	SLB15785 + SLK22013 + SLK290	
光源	LLD2421LCB1 ×1                      500.0 lm	
管理番号	K0193248 (0) DB1	
BZ分類	BZ2/1.1/BZ3/6.0/BZ4	

器具効率	86%	天井	80%				70%				50%				30%				0%		
	上方光束		15%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		71%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	5.4	4.6	4.1	3.7	5.3	4.5	4.0	3.7	5.0	4.3	3.9	3.6	4.7	4.1	3.8	3.5	3.2	
	中	0.6	0.8	6.2	5.4	4.8	4.4	6.0	5.2	4.7	4.4	5.6	5.0	4.6	4.3	5.3	4.8	4.4	4.1	3.9	
	否	0.56	1.0	6.6	5.9	5.4	5.0	6.4	5.7	5.3	4.9	6.0	5.5	5.1	4.7	5.7	5.2	4.9	4.6	4.3	
	下方投影面積	cm <sup>2</sup>		1.25	7.0	6.4	5.9	5.5	6.8	6.2	5.7	5.4	6.4	5.9	5.5	5.2	6.0	5.6	5.3	5.0	4.7
取付高さ	器具間隔最大限		1.5	7.3	6.7	6.2	5.9	7.1	6.5	6.1	5.8	6.6	6.2	5.8	5.5	6.2	5.9	5.6	5.3	5.0	
	横方向 (A)	縦方向 (B)	2.0	7.7	7.2	6.8	6.4	7.4	7.0	6.6	6.3	7.0	6.6	6.3	6.0	6.6	6.3	6.0	5.8	5.4	
Hm	0.64Hm	0.64Hm	2.5	7.9	7.5	7.1	6.8	7.7	7.3	6.9	6.7	7.2	6.9	6.6	6.4	6.8	6.5	6.3	6.1	5.6	
			3.0	8.1	7.7	7.4	7.1	7.8	7.5	7.2	6.9	7.4	7.1	6.8	6.6	6.9	6.7	6.5	6.3	5.8	
			4.0	8.3	8.0	7.7	7.5	8.0	7.8	7.5	7.3	7.6	7.3	7.1	7.0	7.1	6.9	6.8	6.6	6.1	
			5.0	8.4	8.2	7.9	7.7	8.2	7.9	7.7	7.5	7.7	7.5	7.3	7.2	7.2	7.1	6.9	6.8	6.3	
			7.0	8.6	8.4	8.2	8.0	8.3	8.1	8.0	7.8	7.8	7.7	7.6	7.4	7.4	7.3	7.1	7.1	6.5	
			10.0	8.7	8.5	8.4	8.3	8.4	8.3	8.2	8.1	7.9	7.8	7.7	7.6	7.5	7.4	7.3	7.2	6.6	

