

# 屋内照明器具特性

|         |   |  |  |  |  |
|---------|---|--|--|--|--|
| 品番 (品名) | SLB15785 + SLK22013 + SLK290                  |  |  |  |  |
| 光源      | LLD3421LCB1 ×1                      700.0 1 m |  |  |  |  |
| 管理番号    | K0193059 ( 0 ) DB 1                           |  |  |  |  |
| BZ分類    | BZ4 / 0.7 / BZ5 / 3.5 / BZ6                   |  |  |  |  |

|        |                  |          |                  |      |    |      |      |    |    |      |      |    |    |      |      |    |    |      |     |    |     |
|--------|------------------|----------|------------------|------|----|------|------|----|----|------|------|----|----|------|------|----|----|------|-----|----|-----|
| 器具効率   | 87 %             | 天井       | 80 %             |      |    |      | 70 % |    |    |      | 50 % |    |    |      | 30 % |    |    |      | 0 % |    |     |
|        | 上方光束             |          | 25 %             | 壁    | 70 | 50   | 30   | 10 | 70 | 50   | 30   | 10 | 70 | 50   | 30   | 10 | 70 | 50   | 30  | 10 | 0 % |
|        | 下方光束             |          | 62 %             |      | 床  | 10 % |      |    |    | 10 % |      |    |    | 10 % |      |    |    | 10 % |     |    |     |
| 室指数    | 照明率 ( X0.01 )    |          |                  |      |    |      |      |    |    |      |      |    |    |      |      |    |    |      |     |    | ZCM |
| 保守率    | 良                | 0.63     | 0.6              | 0.6  | 47 | 37   | 31   | 26 | 45 | 36   | 30   | 26 | 40 | 33   | 28   | 24 | 36 | 30   | 26  | 23 | 20  |
|        | 中                | 0.6      | 0.6              | 0.6  | 54 | 44   | 38   | 33 | 51 | 42   | 36   | 32 | 46 | 39   | 34   | 30 | 41 | 36   | 31  | 28 | 24  |
|        | 否                | 0.56     | 0.56             | 0.56 | 59 | 50   | 43   | 38 | 56 | 47   | 42   | 37 | 50 | 43   | 38   | 34 | 45 | 39   | 35  | 32 | 27  |
|        |                  |          |                  |      | 63 | 55   | 48   | 43 | 60 | 52   | 46   | 42 | 54 | 48   | 43   | 39 | 48 | 43   | 39  | 36 | 31  |
| 下方投影面積 | c m <sup>2</sup> |          | 1.25             | 66   | 59 | 53   | 48   | 63 | 56 | 50   | 46   | 57 | 51 | 46   | 43   | 51 | 46 | 42   | 39  | 33 |     |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0  | 71 | 64   | 59   | 54 | 67 | 61   | 56   | 52 | 61 | 56   | 52   | 48 | 54 | 50   | 47  | 44 | 38  |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 74   | 68 | 63   | 58   | 70 | 65 | 60   | 56   | 63 | 59 | 55   | 52   | 57 | 53 | 50   | 48  | 41 |     |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 76   | 70 | 66   | 62   | 72 | 67 | 63   | 59   | 65 | 61 | 58   | 55   | 58 | 55 | 53   | 50  | 43 |     |
| H m    | 0.49 H m         | 0.49 H m | 4.0              | 78   | 74 | 70   | 67   | 75 | 71 | 67   | 64   | 67 | 64 | 61   | 59   | 61 | 58 | 56   | 54  | 46 |     |
|        |                  |          | 5.0              | 80   | 76 | 73   | 70   | 76 | 73 | 70   | 67   | 69 | 66 | 64   | 62   | 62 | 60 | 58   | 56  | 48 |     |
|        |                  |          | 7.0              | 82   | 79 | 77   | 74   | 78 | 76 | 73   | 71   | 71 | 69 | 67   | 65   | 64 | 63 | 61   | 60  | 51 |     |
|        |                  |          | 10.0             | 84   | 82 | 80   | 78   | 80 | 78 | 76   | 74   | 73 | 71 | 70   | 68   | 66 | 65 | 63   | 62  | 53 |     |

