

屋内照明器具特性

品番 (品名)	SLB15785 + SLK22014 + SLK290	
光源	LLD2411LCB1 ×1	500.0 lm
管理番号	K0193681(0)DB1	
BZ分類	BZ1/4.5/BZ2	

器具効率	99%	天井	80%				70%				50%				30%				0%									
	上方光束 7%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%								
下方光束	92%	床		10%				10%				10%				10%				0%								
室指数	照明率 (X0.01)																				ZCM							
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6								
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6								
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56								
下方投影面積	等価発光面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0																
		cm ²		1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0																	
取付高さ	器具間隔最大限		Hm		0.74Hm		0.74Hm																					
0.74Hm	0.74Hm		0.74Hm		0.74Hm		0.74Hm																					

