

屋内照明器具特性

| | | |
|---------|--|--|
| 品番 (品名) | SLB15785 + SLK22014 + SLK290 | |
| 光源 | LLD2401LCB1 ×1 500.0 lm | |
| 管理番号 | K0193687 (0) DB 1 | |
| BZ分類 | BZ4/0.7/BZ3/0.9/BZ4/6.0/BZ5 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|----|-----|
| 器具効率 | 89% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 11% | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 下方光束 | 78% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.63 | 0.6 | 53 | 43 | 37 | 33 | 51 | 42 | 36 | 32 | 48 | 41 | 35 | 32 | 45 | 39 | 34 | 31 | 28 | |
| | 中 | 0.6 | 0.8 | 61 | 52 | 46 | 41 | 59 | 51 | 45 | 41 | 56 | 49 | 44 | 40 | 53 | 47 | 42 | 39 | 36 | |
| | 否 | 0.56 | 1.0 | 67 | 58 | 52 | 48 | 65 | 57 | 51 | 47 | 61 | 54 | 49 | 46 | 57 | 52 | 48 | 44 | 41 | |
| | | | 1.25 | 71 | 64 | 58 | 53 | 69 | 62 | 57 | 53 | 65 | 59 | 55 | 51 | 61 | 56 | 53 | 49 | 46 | |
| 下方投影面積 | cm ² | | 1.5 | 75 | 68 | 62 | 58 | 72 | 66 | 61 | 57 | 68 | 63 | 58 | 55 | 64 | 60 | 56 | 53 | 49 | |
| 等価発光面積 | cm ² | | 2.0 | 79 | 73 | 68 | 64 | 77 | 71 | 67 | 63 | 72 | 68 | 64 | 61 | 68 | 64 | 61 | 59 | 54 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 82 | 76 | 72 | 68 | 79 | 75 | 71 | 67 | 75 | 71 | 68 | 65 | 70 | 67 | 65 | 62 | 58 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 83 | 79 | 75 | 72 | 81 | 77 | 73 | 70 | 77 | 73 | 70 | 68 | 72 | 70 | 67 | 65 | 60 | |
| Hm | 1.05Hm | 0.49Hm | 4.0 | 86 | 82 | 79 | 76 | 83 | 80 | 77 | 75 | 79 | 76 | 74 | 72 | 75 | 72 | 70 | 69 | 64 | |
| | | | 5.0 | 87 | 84 | 82 | 79 | 85 | 82 | 80 | 77 | 80 | 78 | 76 | 74 | 76 | 74 | 73 | 71 | 66 | |
| | | | 7.0 | 89 | 87 | 85 | 83 | 87 | 85 | 83 | 81 | 82 | 80 | 79 | 77 | 78 | 76 | 75 | 74 | 69 | |
| | | | 10.0 | 90 | 89 | 87 | 86 | 88 | 87 | 85 | 84 | 84 | 82 | 81 | 80 | 79 | 78 | 77 | 76 | 71 | |

