

屋内照明器具特性	
品番 (品名)	XLGB1860
光源	LLD20003CQ1 ×1 531.0 lm
管理番号	K0191980 (0) DR 1
BZ分類	BZ4/6.0/BZ5

器具効率		77 % 上方光束 3 % 下方光束 74 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.67	0.6	46	37	32	28	45	37	32	28	43	36	31	28	41	35	31	27	26		
			0.63	0.8	54	45	40	36	52	45	40	36	50	43	39	35	48	42	38	35	33		
			1.0	58	51	45	41	57	50	45	41	55	49	44	41	52	47	43	40	38			
			0.56	1.25	63	56	51	47	61	55	50	46	59	53	49	46	56	52	48	45	43		
下方投影面積		cm ²	1.5	66	59	54	51	64	58	54	50	61	57	53	49	59	55	51	49	46			
等価発光面積			cm ²	2.0	69	64	60	56	68	63	59	56	65	61	58	55	63	59	56	54	52		
取付高さ				器具間隔最大限		2.5	72	67	64	60	70	66	63	60	68	64	61	59	65	62	60	57	55
H m		1.24 H m		縦方向 (B)		3.0	74	70	66	63	72	69	65	63	69	66	64	61	67	64	62	60	57
H m		1.24 H m		4.0	76	73	70	67	74	71	69	66	72	69	67	65	69	67	65	64	61		
				5.0	77	74	72	70	76	73	71	69	73	71	69	67	71	69	67	66	63		
				7.0	79	77	75	73	77	75	74	72	75	73	72	70	72	71	70	69	66		
				10.0	80	78	77	76	78	77	76	75	76	75	74	73	74	73	72	71	68		

