

屋内照明器具特性	
品番 (品名)	XLGB82811
光源	LED3500_70_145 ×1 145.0 lm
管理番号	K0169174 (0) DR 1
BZ分類	BZ4/0.9/BZ3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		31 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		69 %																								
保守率		良 中 否	0.63	0.6	55	44	37	32	52	42	36	31	47	39	33	29	42	36	31	28	24					
			0.6	0.8	65	54	47	42	61	52	46	41	55	48	43	39	50	44	39	36	31					
			0.56	1.0	71	62	55	50	67	59	53	48	61	54	49	45	55	49	45	42	37					
				1.25	77	68	62	57	73	65	59	55	66	60	55	51	59	55	51	48	41					
下方投影面積		cm ²		1.5	80	73	67	62	76	70	64	60	69	64	59	56	62	58	55	52	45					
等価発光面積			cm ²	2.0	85	79	74	70	81	76	71	67	74	69	65	62	66	63	60	58	50					
				2.5	89	83	79	75	84	80	76	72	76	73	69	67	69	66	64	61	53					
取付 高さ	器具間隔最大限		3.0	91	86	82	79	86	82	79	76	78	75	72	70	71	68	66	64	55						
	横方向 (A)			縦方向 (B)		4.0	93	90	86	84	89	86	83	80	81	78	76	74	73	71	69	68	58			
H m	1.15 H m		1.25 H m		5.0	95	92	89	87	91	88	86	83	82	80	78	77	74	73	71	70	60				
					7.0	97	95	93	91	92	91	89	87	84	83	81	80	76	75	74	73	63				
					10.0	98	97	95	94	94	92	91	90	85	84	83	82	77	77	76	75	64				

