

屋内照明器具特性	
品番 (品名)	XLGB82815
光源	LED5000_70_140 ×1 140.0 lm
管理番号	K0169175 (1) DR 1
BZ分類	BZ3

器具効率		100 % 上方光束 30 % 下方光束 70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
			室指数	照明率 (X0.01)																	ZCM	
保守率		良 中 否	0.63	0.6	57	46	39	34	54	44	38	33	49	41	35	31	44	38	33	30	26	
			0.6	0.8	66	56	49	44	63	54	48	43	57	50	45	41	52	46	42	38	34	
			0.56	1.0	72	63	57	52	69	61	55	50	63	56	51	47	57	52	48	44	39	
				1.25	78	70	63	59	74	67	61	57	67	62	57	53	61	57	53	50	44	
下方投影面積		cm ²		1.5	81	74	68	64	78	71	66	62	71	65	61	58	64	60	57	54	47	
等価発光面積			cm ²	2.0	86	80	75	71	82	77	73	69	75	71	67	64	68	65	62	60	52	
				2.5	89	84	80	76	85	81	77	74	78	74	71	68	71	68	65	63	55	
取付 高さ	器具間隔最大限		3.0	91	87	83	80	87	83	80	77	80	77	74	71	72	70	68	66	58		
	横方向 (A)			縦方向 (B)																		
H _m	1.10 H _m	1.22 H _m	4.0	94	91	87	85	90	87	84	82	82	80	77	75	74	73	71	70	61		
			5.0	96	93	90	88	91	89	87	84	83	81	80	78	76	74	73	72	62		
			7.0	97	95	93	91	93	91	90	88	85	84	82	81	77	76	75	74	64		
			10.0	99	97	96	94	94	93	92	91	86	85	84	83	79	78	77	76	66		

