

屋内照明器具特性	
品番 (品名)	XLGB82832
光源	LED2700_70_475 ×1 475.0 lm
管理番号	K0169183 (1) DR 1
BZ分類	BZ5/1.1/BZ4/3.5/BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 7	0 . 6	4 3	3 3	2 6	2 2	3 7	2 8	2 3	1 9	2 5	2 0	1 6	1 3	1 4	1 1	9	8	0				
			0 . 6 3	0 . 8	5 1	4 1	3 4	2 9	4 3	3 5	3 0	2 5	3 0	2 4	2 1	1 8	1 7	1 4	1 2	1 1	0				
			0 . 5 6	1 . 0	5 6	4 7	4 0	3 5	4 8	4 1	3 5	3 1	3 3	2 8	2 5	2 2	1 9	1 6	1 4	1 3	0				
				1 . 2 5	6 2	5 3	4 7	4 2	5 3	4 6	4 0	3 6	3 6	3 2	2 8	2 6	2 1	1 8	1 7	1 5	0				
下方投影面積		c m ²		1 . 5	6 5	5 7	5 1	4 7	5 6	5 0	4 5	4 1	3 8	3 4	3 1	2 9	2 2	2 0	1 8	1 7	0				
			等価発光面積		c m ²	2 . 0	7 0	6 4	5 8	5 4	6 0	5 5	5 1	4 7	4 1	3 8	3 5	3 3	2 4	2 2	2 1	2 0	0		
取付 高さ	器具間隔最大限		2 . 5	7 3	6 8	6 3	5 9	6 3	5 8	5 5	5 1	4 3	4 1	3 8	3 6	2 5	2 4	2 3	2 1	0					
	横方向 (A) 縦方向 (B)		3 . 0	7 5	7 0	6 6	6 3	6 5	6 1	5 7	5 4	4 5	4 2	4 0	3 8	2 6	2 5	2 4	2 3	0					
H m	1 . 0 9 H m 1 . 3 7 H m		4 . 0	7 8	7 4	7 1	6 8	6 7	6 4	6 1	5 9	4 7	4 5	4 3	4 1	2 7	2 6	2 5	2 4	0					
			5 . 0	8 0	7 6	7 4	7 1	6 9	6 6	6 4	6 2	4 8	4 6	4 5	4 3	2 8	2 7	2 6	2 6	0					
			7 . 0	8 2	7 9	7 7	7 5	7 0	6 9	6 7	6 5	4 9	4 8	4 7	4 6	2 9	2 8	2 8	2 7	0					
			1 0 . 0	8 3	8 1	8 0	7 8	7 2	7 0	6 9	6 8	5 0	4 9	4 8	4 8	2 9	2 9	2 9	2 8	0					

