

# 屋内照明器具特性

品番 (品名)	XLX465GHVP														
光源	LED3500_85_5750 x1 5750.0 lm														
管理番号	K0134370(3)DB1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	5%	室指数	照明率 ( X0.01 ) ZCM																		
下方光束	95%	良	0.6	5.9	4.8	4.0	3.5	5.8	4.7	4.0	3.5	5.5	4.6	3.9	3.5	5.2	4.4	3.9	3.4	3.2	
		中	0.8	6.9	5.9	5.2	4.6	6.8	5.8	5.1	4.6	6.5	5.6	5.0	4.6	6.2	5.4	4.9	4.5	4.2	
		否	1.0	7.6	6.6	6.0	5.4	7.4	6.5	5.9	5.4	7.1	6.3	5.8	5.3	6.8	6.1	5.6	5.2	5.0	
			1.25	8.2	7.3	6.7	6.2	8.0	7.2	6.6	6.1	7.6	7.0	6.4	6.0	7.3	6.8	6.3	5.9	5.6	
下方投影面積	c m <sup>2</sup>		1.5	8.6	7.8	7.2	6.7	8.4	7.7	7.1	6.7	8.0	7.4	6.9	6.5	7.7	7.2	6.8	6.4	6.1	
等価発光面積		c m <sup>2</sup>	2.0	9.1	8.5	7.9	7.5	8.9	8.3	7.8	7.4	8.5	8.0	7.6	7.3	8.2	7.8	7.4	7.1	6.8	
取付高さ	器具間隔最大限		2.5	9.4	8.9	8.4	8.0	9.2	8.7	8.3	7.9	8.8	8.4	8.1	7.8	8.5	8.2	7.9	7.6	7.3	
	横方向 (A)	縦方向 (B)	3.0	9.6	9.2	8.8	8.4	9.4	9.0	8.6	8.3	9.1	8.7	8.4	8.1	8.7	8.4	8.2	7.9	7.6	
1.5m	1.86m	2.2m	4.0	9.9	9.5	9.2	8.9	9.7	9.4	9.1	8.8	9.3	9.1	8.8	8.6	9.0	8.8	8.6	8.4	8.0	
2	2.47	2.78	5.0	10.1	9.8	9.5	9.2	9.9	9.6	9.3	9.1	9.5	9.3	9.1	8.9	9.2	9.0	8.8	8.7	8.3	
2.5	3.08	3.38	7.0	10.2	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.5	9.4	9.2	9.4	9.2	9.1	9.0	8.6	
3	3.68	3.99	10.0	10.4	10.2	10.1	9.9	10.2	10.1	9.9	9.8	9.9	9.7	9.6	9.5	9.5	9.4	9.3	9.2	8.8	

