

屋内照明器具特性	
品番 (品名)	XLGB82905
光源	LED5000_70_220 ×1 220.0 lm
管理番号	K0169179 (0) DR 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.63	0.6	50	39	32	27	47	37	30	26	39	32	26	23	33	27	23	20	15	
			0.6	0.8	60	49	42	37	55	46	39	35	47	40	35	31	39	34	30	27	21	
			0.56	1.0	66	56	49	44	61	53	46	42	52	46	41	37	44	39	35	32	25	
				1.25	72	63	56	51	66	59	53	48	57	51	46	43	48	43	40	37	29	
下方投影面積		cm ²	1.5	75	67	61	56	70	63	58	53	60	55	50	47	50	47	43	41	31		
			等価発光面積		cm ²	2.0	81	74	69	64	75	69	64	60	64	60	56	53	54	51	48	46
取付 高さ	器具間隔最大限		2.5	84	78	73	69	78	73	69	65	67	63	60	57	56	54	51	49	38		
	横方向 (A)	縦方向 (B)	3.0	86	81	77	73	80	76	72	69	69	66	63	60	58	56	54	52	39		
H _m	0.00 H _m	1.67 H _m	4.0	89	85	82	78	83	79	76	74	71	69	66	64	60	58	57	55	42		
			5.0	91	87	84	82	84	82	79	77	73	71	69	67	61	60	59	57	43		
			7.0	92	90	88	86	86	84	82	80	74	73	71	70	63	62	61	60	45		
			10.0	94	92	91	89	88	86	85	83	76	75	73	72	64	63	63	62	47		

