

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XLGB82920                  |
| 光源       | LED5000_70_185 ×1 185.0 lm |
| 管理番号     | K0169182 ( 1 ) DR 1        |
| BZ分類     | BZ5 / 0.7 / BZ4            |

| 器具効率           |                    | 100 %              | 反射率  | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |     |  |
|----------------|--------------------|--------------------|------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|-----|--|
|                |                    |                    |      | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |     |  |
|                |                    |                    |      | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |     |  |
| 上方光束           |                    | 50 %               | 室指数  | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | ZCM |  |
| 下方光束           |                    | 50 %               |      |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |     |  |
| 保守率            |                    | 良<br>中<br>否        | 0.63 | 0.6           | 51   | 40 | 33 | 28 | 47   | 37 | 31 | 26 | 40   | 32 | 27 | 23 | 33   | 28 | 24 | 21 | 16  |  |     |  |
|                |                    |                    | 0.6  | 0.8           | 60   | 50 | 43 | 37 | 56   | 47 | 40 | 36 | 47   | 40 | 35 | 32 | 40   | 35 | 31 | 28 | 21  |  |     |  |
|                |                    |                    |      | 1.0           | 66   | 57 | 50 | 45 | 62   | 53 | 47 | 42 | 52   | 46 | 41 | 38 | 44   | 40 | 36 | 33 | 25  |  |     |  |
|                |                    |                    | 0.56 | 1.25          | 72   | 63 | 57 | 52 | 67   | 59 | 54 | 49 | 57   | 51 | 47 | 44 | 48   | 44 | 41 | 38 | 29  |  |     |  |
| 下方投影面積         |                    | cm <sup>2</sup>    |      | 1.5           | 76   | 68 | 62 | 57 | 70   | 64 | 58 | 54 | 60   | 55 | 51 | 48 | 51   | 47 | 44 | 42 | 32  |  |     |  |
|                |                    |                    |      | 2.0           | 81   | 75 | 69 | 65 | 75   | 70 | 65 | 61 | 64   | 60 | 57 | 54 | 54   | 51 | 49 | 47 | 36  |  |     |  |
| 等価発光面積         |                    | cm <sup>2</sup>    |      | 2.5           | 84   | 79 | 74 | 70 | 78   | 73 | 69 | 66 | 67   | 64 | 61 | 58 | 57   | 54 | 52 | 50 | 38  |  |     |  |
|                |                    |                    |      | 3.0           | 86   | 82 | 77 | 74 | 80   | 76 | 73 | 69 | 69   | 66 | 63 | 61 | 58   | 56 | 54 | 52 | 40  |  |     |  |
| H <sub>m</sub> | 0.00H <sub>m</sub> | 1.63H <sub>m</sub> |      | 4.0           | 89   | 85 | 82 | 79 | 83   | 80 | 77 | 74 | 71   | 69 | 67 | 65 | 60   | 59 | 57 | 56 | 42  |  |     |  |
|                |                    |                    |      | 5.0           | 91   | 88 | 85 | 82 | 84   | 82 | 79 | 77 | 73   | 71 | 69 | 67 | 61   | 60 | 59 | 58 | 44  |  |     |  |
|                |                    |                    |      | 7.0           | 93   | 90 | 88 | 86 | 86   | 84 | 83 | 81 | 74   | 73 | 72 | 70 | 63   | 62 | 61 | 60 | 45  |  |     |  |
|                |                    |                    |      | 10.0          | 94   | 92 | 91 | 89 | 88   | 86 | 85 | 84 | 76   | 75 | 74 | 73 | 64   | 63 | 63 | 62 | 46  |  |     |  |

