

屋内照明器具特性	
品番 (品名)	XLGB1051
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0189910 (2) DR1
BZ分類	BZ4/6.0/BZ5

器具効率		81 % 上方光束 3 % 下方光束 78 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.67	0.6	48	39	33	29	47	39	33	29	45	38	32	29	43	37	32	28	27	
			0.63	0.8	56	48	42	38	55	47	41	37	53	46	41	37	50	44	40	37	35	
			0.56	1.0	61	53	48	43	60	53	47	43	57	51	46	43	55	50	45	42	40	
			1.25	66	59	53	49	64	58	53	49	62	56	52	48	59	54	50	47	45		
下方投影面積		cm ²	1.5	69	62	57	53	67	61	57	53	64	59	55	52	62	58	54	51	49		
			2.0	73	67	63	59	71	66	62	59	68	64	61	58	66	62	59	57	54		
等価発光面積		cm ²	2.5	75	71	67	63	74	70	66	63	71	67	64	61	68	65	63	60	58		
			3.0	77	73	69	66	76	72	69	66	73	70	67	64	70	67	65	63	60		
H m	1.26 H m		1.26 H m		4.0	79	76	73	71	78	75	72	70	75	73	70	68	73	70	68	67	64
				5.0	81	78	76	73	79	77	75	72	77	74	72	71	74	72	71	69	66	
				7.0	82	80	78	77	81	79	77	76	78	77	75	74	76	74	73	72	69	
				10.0	84	82	81	79	82	81	80	78	80	78	77	76	77	76	75	74	71	

