

屋内照明器具特性	
品番 (品名)	XLGB1053
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0189911 (2) DR1
BZ分類	BZ4/0.7/BZ3/1.1/BZ4

器具効率		76 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		2 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		74 %																							
保守率		良 中 否	0.67	0.6	46	38	32	29	45	37	32	29	43	36	32	28	42	36	31	28	27				
			0.63	0.8	54	46	41	37	53	45	40	37	51	44	40	36	49	43	39	36	34				
			0.56	1.0	59	51	46	42	57	51	46	42	55	49	45	42	53	48	44	41	39				
			1.25	63	56	51	47	61	55	51	47	59	54	50	47	57	52	49	46	44					
下方投影面積		cm ²	1.5	66	60	55	51	64	59	54	51	62	57	53	50	59	55	52	49	47					
			2.0	69	64	60	57	68	63	60	56	65	62	58	55	63	60	57	55	52					
等価発光面積		cm ²	2.5	72	67	64	61	70	66	63	60	68	64	62	59	65	63	60	58	56					
			3.0	73	69	66	63	72	68	65	63	69	66	64	62	67	65	62	60	58					
H	m	1.24 H	m	1.24 H	m	4.0	75	72	70	67	74	71	69	67	71	69	67	65	64	61					
						5.0	77	74	72	70	75	73	71	69	73	71	69	67	70	69	66				
						7.0	78	76	74	73	77	75	73	72	74	73	72	70	72	71	70	69	66		
						10.0	79	78	76	75	78	77	75	74	76	74	73	72	73	72	72	71	68		

