

屋内照明器具特性

品番 (品名)		XLGE532BHF																			
光源		LDA4L-H-E17/S/4×1440.0lm																			
管理番号		K0158843 (0)DB1																			
BZ分類		BZ10																			
器具効率 上方光束 下方光束		28 % 15 % 13 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01)ZCM																	
保守率		良0.63 中0.6 否0.56	0.6	11	8	5	4	10	7	5	3	8	5	4	2	6	4	3	2	0	
			0.8	13	10	7	5	12	9	7	5	10	7	5	4	7	5	4	3	1	
			1.0	15	11	9	7	13	10	8	6	11	8	6	5	8	6	5	4	1	
下方投影面積 等価発光面積		cm ² cm ²	1.25	16	13	11	9	15	12	10	8	12	9	8	6	9	7	6	5	2	
			1.5	18	14	12	10	16	13	11	9	13	11	9	7	10	8	7	6	3	
取付高さ		器具間隔最大限 横方向 (A)縦方向 (B)	2.0	19	16	14	12	17	15	13	11	14	12	10	9	11	9	8	7	4	
			2.5	20	18	16	14	18	16	14	13	15	13	12	10	12	10	9	8	5	
H _m		0.00H _m 0.00H _m	3.0	21	19	17	15	19	17	15	14	16	14	13	11	12	11	10	9	5	
H _m		0.00H _m 0.00H _m	4.0	22	20	18	17	20	19	17	16	17	15	14	13	13	12	11	10	6	
			5.0	23	21	20	18	21	19	18	17	17	16	15	14	14	13	12	11	7	
			7.0	24	22	21	20	22	21	19	18	18	17	16	15	15	14	13	13	8	
			10.0	24	23	22	21	22	22	21	20	19	18	17	17	15	15	14	14	9	

