

屋内照明器具特性	
品番 (品名)	XLGB1400
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0176189 (0) DR1
BZ分類	BZ5

器具効率		71 % 上方光束 4 % 下方光束 67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	39	30	25	21	38	30	24	21	36	29	24	20	34	28	23	20	18	
			0.63	0.8	46	38	32	28	45	37	31	28	42	36	31	27	40	34	30	27	25	
			0.56	1.0	51	43	37	33	49	42	37	33	47	40	36	32	44	39	35	31	29	
			1.25	55	48	42	38	53	47	42	38	51	45	41	37	48	43	39	36	34		
下方投影面積		cm ²	1.5	58	51	46	42	56	50	45	42	53	48	44	41	51	47	43	40	38		
			2.0	62	56	52	48	60	55	51	48	57	53	50	46	55	51	48	45	43		
取付 高さ	器具間隔最大限		2.5	64	60	56	52	63	59	55	52	60	56	53	50	57	54	52	49	47		
	横方向 (A)		縦方向 (B)		3.0	66	62	58	55	65	61	58	55	62	59	56	53	59	57	54	52	49
H m	1.17 H m		1.17 H m		4.0	68	65	62	60	67	64	61	59	64	62	59	57	60	58	56	53	
					5.0	70	67	65	62	68	66	64	62	66	64	62	60	63	61	60	58	55
					7.0	72	69	68	66	70	68	66	65	68	66	64	63	65	64	62	61	58
					10.0	73	71	70	69	71	70	69	67	69	68	67	66	66	65	65	64	61

