

| 屋内照明器具特性 |                                         |
|----------|-----------------------------------------|
| 品番 (品名)  | S N C 3 8 2 0 2                         |
| 光源       | LED6200_70_4299 ×1 4299.0 lm            |
| 管理番号     | K0181799 ( 0 ) DR 1                     |
| B Z 分類   | BZ6 / 1.1 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5 |

| 器具効率         |                     | 100 %           | 天井<br>反射率 | 80 %              |      |    |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|--------------|---------------------|-----------------|-----------|-------------------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
|              |                     |                 |           | 壁                 | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |
|              |                     |                 |           | 床                 | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
| 上方光束<br>下方光束 |                     | 26 %<br>74 %    | 室指数       | 照明率 ( X0.01 ) ZCM |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率          |                     | 良<br>中<br>否     |           | 0.6               | 51   | 39 | 31 | 26   | 48   | 37 | 30 | 25   | 44   | 34 | 28 | 23   | 39   | 31 | 26 | 22  | 18  |
|              |                     |                 | 0.8       | 60                | 48   | 40 | 35 | 57   | 46   | 39 | 34 | 51   | 43   | 36 | 31 | 46   | 39   | 34 | 29 | 25  |     |
|              |                     |                 | 1.0       | 67                | 55   | 47 | 41 | 63   | 53   | 46 | 40 | 57   | 49   | 42 | 38 | 51   | 44   | 39 | 35 | 30  |     |
|              |                     |                 | 0.56      | 1.25              | 72   | 62 | 54 | 48   | 69   | 59 | 52 | 47   | 62   | 54 | 48 | 44   | 56   | 50 | 45 | 41  | 35  |
| 下方投影面積       |                     | cm <sup>2</sup> | 1.5       | 76                | 67   | 60 | 54 | 73   | 64   | 57 | 52 | 66   | 59   | 53 | 49 | 59   | 54   | 49 | 45 | 39  |     |
| 等価発光面積       |                     | cm <sup>2</sup> | 2.0       | 82                | 74   | 67 | 62 | 78   | 71   | 65 | 60 | 71   | 65   | 60 | 56 | 64   | 59   | 55 | 52 | 45  |     |
| 取付<br>高さ     | 器具間隔最大限             |                 | 2.5       | 86                | 79   | 73 | 68 | 82   | 75   | 70 | 65 | 74   | 69   | 65 | 61 | 67   | 63   | 60 | 56 | 49  |     |
|              | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0       | 88                | 82   | 77 | 72 | 84   | 79   | 74 | 70 | 77   | 72   | 68 | 65 | 70   | 66   | 63 | 60 | 52  |     |
| 1.5m         | 2.02 m              | 1.95 m          | 4.0       | 91                | 86   | 82 | 78 | 87   | 83   | 79 | 75 | 80   | 76   | 73 | 70 | 73   | 70   | 67 | 65 | 56  |     |
| 2            | 2.66                | 2.56            | 5.0       | 94                | 89   | 86 | 82 | 90   | 86   | 82 | 79 | 82   | 79   | 76 | 73 | 75   | 72   | 70 | 68 | 59  |     |
| 2.5          | 3.32                | 3.19            | 7.0       | 96                | 93   | 90 | 87 | 92   | 89   | 86 | 84 | 84   | 82   | 80 | 78 | 77   | 75   | 73 | 72 | 63  |     |
| 3            | 3.94                | 3.8             | 10.0      | 98                | 95   | 93 | 91 | 94   | 92   | 90 | 88 | 86   | 85   | 83 | 81 | 79   | 78   | 76 | 75 | 66  |     |

