

屋内照明器具特性	
品番 (品名)	XLJ 4101
光源	LED5000_92_2750 ×1 2750.0 lm
管理番号	K0154135 (2) DY1
BZ分類	BZ5

器具効率		100 % 上方光束 3 % 下方光束 97 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.9	0.6	56	43	35	30	54	43	35	30	51	41	34	29	49	40	34	29	27	
			0.87	0.8	65	54	46	40	64	53	45	40	61	51	44	39	58	49	43	39	36	
			0.83	1.0	72	61	53	47	70	60	52	47	67	58	51	46	64	56	50	46	43	
				1.25	78	68	60	54	76	67	60	54	72	64	58	53	69	62	57	52	50	
下方投影面積		cm ²		1.5	82	73	66	60	80	72	65	59	76	69	63	58	73	67	62	58	55	
			等価発光面積	cm ²	2.0	88	80	73	68	86	78	72	68	82	76	71	66	78	73	69	65	62
取付 高さ	器具間隔最大限			2.5	91	84	79	74	89	83	78	73	85	80	76	72	82	78	74	70	67	
	横方向 (A)		縦方向 (B)	3.0	94	88	83	78	92	86	81	77	88	83	79	76	85	81	77	74	71	
H m	1.27 H m		1.27 H m	4.0	97	92	88	84	95	90	87	83	91	88	84	81	88	85	82	79	76	
				5.0	99	95	91	88	97	93	90	87	93	90	87	85	90	88	85	83	79	
				7.0	101	98	95	92	99	96	94	91	96	94	91	89	93	91	89	87	83	
				10.0	103	101	98	96	101	99	97	95	98	96	94	93	95	93	92	91	87	

