

屋内照明器具特性	
品番 (品名)	X F L 3 2 3 P F
光源	LDL40S. N/ 14/ 26 (2600A) ×2 2600.0 lm
管理番号	K0126762 (5) DR 1
B Z 分類	BZ5

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		64 %																					
保守率		良 中 否	0.77	0.6	36	29	23	20	36	28	23	20	34	27	23	20	33	27	23	20	18		
			0.72	0.8	43	35	30	27	42	35	30	27	40	34	30	26	38	33	29	26	25		
			0.68	1.0	47	40	35	31	46	40	35	31	44	38	34	31	42	37	34	31	29		
				1.25	51	45	40	36	50	44	39	36	48	43	39	36	46	42	38	35	34		
下方投影面積		cm ²	1.5	54	48	43	40	52	47	43	40	50	46	42	39	48	45	41	39	37			
等価発光面積			2.0	57	52	48	45	56	52	48	45	54	50	47	44	52	49	46	44	42			
取付 高さ	器具間隔最大限		2.5	59	55	52	49	58	54	51	48	56	53	50	48	54	52	49	47	45			
	横方向 (A)		縦方向 (B)	3.0	61	57	54	51	60	57	54	51	58	55	53	50	56	54	52	50	48		
1.5m	1.93 m	2.13 m	4.0	63	60	57	55	62	59	57	55	60	58	56	54	58	56	55	53	51			
2	2.55	2.68	5.0	64	62	60	58	63	61	59	57	61	59	58	56	60	58	57	55	53			
2.5	3.17	3.25	7.0	66	64	62	61	65	63	61	60	63	61	60	59	61	60	59	58	56			
3	3.78	3.84	10.0	67	65	64	63	66	65	63	62	64	63	62	61	62	62	61	60	58			

