

屋内照明器具特性	
品番 (品名)	XFL326EZ
光源	LDL40S.N/14/26(2600A) ×2 2600.0lm
管理番号	K0126647(5)DB1
BZ分類	BZ3/0.7/BZ2

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		63 %																								
保守率		良 中 否	0.81	0.6	40	34	30	27	40	34	29	27	38	33	29	27	37	32	29	26	25					
			0.77	0.8	47	42	38	35	47	41	37	35	45	40	37	34	44	40	37	34	33					
			0.68	1.0	52	46	43	40	51	46	42	40	49	45	42	40	48	44	42	39	38					
				1.25	55	50	47	44	54	50	47	44	53	49	46	44	51	48	46	44	42					
下方投影面積		cm ²	1.5	57	53	50	47	56	53	50	47	55	52	49	47	53	51	48	46	45						
			等価発光面積		cm ²	2.0	60	57	54	52	59	56	54	51	57	55	53	51	56	54	52	50	49			
取付 高さ	器具間隔最大限		2.5	62	59	57	55	61	58	56	54	59	57	55	54	58	56	54	53	52						
	横方向 (A) 縦方向 (B)		3.0	63	60	58	57	62	60	58	56	60	58	57	55	59	57	56	55	53						
1.5m	2.4m	2.01m	4.0	64	62	61	59	63	62	60	59	62	60	59	58	60	59	58	57	56						
2	3.19	2.52	5.0	65	63	62	61	64	63	61	60	63	61	60	59	61	60	59	58	57						
2.5	3.98	3.05	7.0	66	65	64	63	65	64	63	62	64	63	62	61	62	61	61	60	58						
3	4.76	3.58	10.0	67	66	65	64	66	65	64	64	64	64	63	63	63	62	62	61	60						

