

屋内照明器具特性	
品番 (品名)	XF Y6 6 0 0 J
光源	LDL40S.N/29/38(3800A) ×6 3800.0 lm
管理番号	K0125273(0)DC1
BZ分類	BZ5

器具効率		61 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.86	0.6	34	27	22	19	34	27	22	19	32	26	22	19	31	25	21	19	18
			0.81	0.8	40	33	29	25	39	33	28	25	38	32	28	25	36	31	28	25	24
			0.76	1.0	44	38	33	30	43	37	33	30	42	36	32	29	40	35	32	29	28
				1.25	48	42	38	34	47	41	37	34	45	40	37	34	43	39	36	33	32
下方投影面積 等価発光面積		cm ²		1.5	50	45	41	38	49	44	41	37	47	43	40	37	46	42	39	37	35
			cm ²	2.0	54	49	46	43	53	49	45	42	51	47	44	42	49	46	43	41	40
取付 高さ	器具間隔最大限			2.5	56	52	49	46	55	51	48	46	53	50	47	45	51	49	46	44	43
	横方向 (A) 縦方向 (B)			3.0	57	54	51	49	56	53	51	48	55	52	50	47	53	51	49	47	45
1.5m	2.32 m	2.28 m		4.0	59	57	54	52	58	56	54	52	56	54	52	51	55	53	51	50	48
2	2.85	2.79		5.0	60	58	56	54	59	57	55	54	58	56	54	53	56	55	53	52	50
2.5	3.41	3.34		7.0	62	60	58	57	61	59	58	56	59	58	57	55	58	56	55	54	53
3	3.99	3.9		10.0	63	61	60	59	62	61	60	59	60	59	58	57	59	58	57	56	55

