

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XLGB1700                |
| 光源       | LLD4000LCE1 ×1 845.0 lm |
| 管理番号     | K0176189 (0) DR1        |
| BZ分類     | BZ5                     |

| 器具効率             |           | 71 %<br><br>上方光束<br>4 %<br>下方光束<br>67 % | 反射率  | 天井   | 80 %             |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|------------------|-----------|-----------------------------------------|------|------|------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                  |           |                                         |      | 壁    | 70               | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                  |           |                                         |      | 床    | 10 %             |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                  |           |                                         |      | 室指数  | 照明率 ( X0.01) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率              |           | 良<br>中<br>否                             | 0.67 | 0.6  | 39               | 30 | 25 | 21 | 38   | 30 | 24 | 21 | 36   | 29 | 24 | 20 | 34   | 28 | 23 | 20 | 18  |
|                  |           |                                         | 0.63 | 0.8  | 46               | 38 | 32 | 28 | 45   | 37 | 31 | 28 | 42   | 36 | 31 | 27 | 40   | 34 | 30 | 27 | 25  |
|                  |           |                                         | 1.0  | 51   | 43               | 37 | 33 | 49 | 42   | 37 | 33 | 47 | 40   | 36 | 32 | 44 | 39   | 35 | 31 | 29 |     |
|                  |           |                                         | 0.56 | 1.25 | 55               | 48 | 42 | 38 | 53   | 47 | 42 | 38 | 51   | 45 | 41 | 37 | 48   | 43 | 39 | 36 | 34  |
| 下方投影面積<br>等価発光面積 |           | cm <sup>2</sup><br><br>cm <sup>2</sup>  | 1.5  | 58   | 51               | 46 | 42 | 56 | 50   | 45 | 42 | 53 | 48   | 44 | 41 | 51 | 47   | 43 | 40 | 38 |     |
|                  |           |                                         | 2.0  | 62   | 56               | 52 | 48 | 60 | 55   | 51 | 48 | 57 | 53   | 50 | 46 | 55 | 51   | 48 | 45 | 43 |     |
|                  |           |                                         | 2.5  | 64   | 60               | 56 | 52 | 63 | 59   | 55 | 52 | 60 | 56   | 53 | 50 | 57 | 54   | 52 | 49 | 47 |     |
| 取付<br>高さ         | 器具間隔最大限   |                                         | 2.5  | 64   | 60               | 56 | 52 | 63 | 59   | 55 | 52 | 60 | 56   | 53 | 50 | 57 | 54   | 52 | 49 | 47 |     |
|                  | 横方向 ( A ) | 縦方向 ( B )                               | 3.0  | 66   | 62               | 58 | 55 | 65 | 61   | 58 | 55 | 62 | 59   | 56 | 53 | 59 | 57   | 54 | 52 | 49 |     |
| H m              | 1.17 H m  | 1.17 H m                                | 4.0  | 68   | 65               | 62 | 60 | 67 | 64   | 61 | 59 | 64 | 62   | 59 | 57 | 62 | 60   | 58 | 56 | 53 |     |
|                  |           |                                         | 5.0  | 70   | 67               | 65 | 62 | 68 | 66   | 64 | 62 | 66 | 64   | 62 | 60 | 63 | 61   | 60 | 58 | 55 |     |
|                  |           |                                         | 7.0  | 72   | 69               | 68 | 66 | 70 | 68   | 66 | 65 | 68 | 66   | 64 | 63 | 65 | 64   | 62 | 61 | 58 |     |
|                  |           |                                         | 10.0 | 73   | 71               | 70 | 69 | 71 | 70   | 69 | 67 | 69 | 68   | 67 | 66 | 66 | 65   | 65 | 64 | 61 |     |

