

屋内照明器具特性	
品番 (品名)	XLGB1732
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0185514 (0) DR1
BZ分類	BZ4/0.7/BZ3/2.8/BZ2/4.5/BZ3 /6.0/BZ2

器具効率		67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		67 %																							
保守率		良 中 否	0.67	0.6	42	34	29	26	41	34	29	26	39	33	29	26	38	33	29	26	25				
			0.63	0.8	49	43	38	35	48	42	38	35	47	41	37	34	45	40	37	34	33				
			0.56	1.0	54	48	44	41	53	48	44	41	51	47	43	40	50	46	43	40	39				
				1.25	58	53	49	46	57	52	49	46	55	51	48	46	54	50	48	45	44				
下方投影面積		cm ²	1.5	61	56	52	50	60	55	52	49	58	54	51	49	56	53	51	49	47					
等価発光面積		cm ²	2.0	64	60	57	55	63	59	57	54	61	58	56	54	60	57	55	53	52					
取付 高さ	器具間隔最大限		2.5	66	63	60	58	65	62	60	58	63	61	59	57	61	59	58	56	55					
	横方向 (A)		縦方向 (B)		3.0	67	64	62	60	66	64	62	60	64	62	61	59	63	61	60	58	57			
H m	1.22 H m	1.22 H m	4.0	68	66	65	63	68	66	64	63	66	64	63	62	64	63	62	61	59					
			5.0	69	68	66	65	69	67	66	64	67	66	64	63	65	64	63	62	61					
			7.0	70	69	68	67	70	68	67	66	68	67	66	65	66	66	65	64	62					
			10.0	71	70	70	69	70	70	69	68	69	68	67	67	67	67	66	66	64					

