

屋内照明器具特性

品番 (品名)	XLX850AELC														
光源	LED3000_85_4610 x1 4610.0 lm														
管理番号	K0128261 (*) DB 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	4 %	室指数	照明率 (X0.01)																ZCM		
下方光束	96 %																				
保守率	良 中 否	0.83	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	25	
		0.81	0.8	64	53	44	38	63	52	44	38	59	50	43	38	56	48	42	37	35	
		0.77	1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	49	44	41	
			1.25	77	67	59	53	75	65	58	52	71	63	57	52	68	61	55	51	48	
下方投影面積	c m ²	1.5	81	72	64	58	79	70	63	58	75	68	62	57	71	65	60	56	53		
		2.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60		
取付高さ	器具間隔最大限		2.5	90	83	77	72	88	82	76	72	84	79	74	70	81	76	72	69	65	
	横方向 (A)	縦方向 (B)	3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	76	73	69	
1.5m	2.09 m	2.89 m	4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74	
2	2.72	3.32	5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	78	
2.5	3.36	3.82	7.0	101	97	94	92	99	96	93	90	95	93	90	88	92	89	88	86	82	
3	4	4.35	10.0	102	100	98	96	101	98	96	94	97	95	93	92	94	92	91	89	85	

