

# 屋内照明器具特性

品番 (品名)	XLY045HYN	
光源	LED5000_85_1140 ×1	1140.0 lm
管理番号	K0155410(0)DB1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	6 %	室指数																	照明率 ( X0.01 )																	ZCM																
下方光束	94 %																																																			
保守率	良 中 否	0.83	0.6	5.4	4.2	3.4	2.8	5.3	4.1	3.3	2.8	5.0	3.9	3.3	2.8	4.7	3.8	3.2	2.7	2.5																																
		0.81	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.8	5.9	4.9	4.2	3.7	5.5	4.7	4.1	3.6	3.4																																
			1.0	7.0	5.9	5.1	4.5	6.8	5.8	5.0	4.5	6.5	5.6	4.9	4.4	6.1	5.3	4.8	4.3	4.0																																
		0.77	1.25	7.6	6.6	5.8	5.2	7.4	6.5	5.7	5.2	7.0	6.2	5.6	5.1	6.6	6.0	5.4	5.0	4.6																																
下方投影面積	c m <sup>2</sup>	1.5	8.0	7.1	6.4	5.8	7.8	6.9	6.3	5.7	7.4	6.7	6.1	5.6	7.0	6.4	5.9	5.5	5.1																																	
		2.0	8.6	7.8	7.1	6.6	8.4	7.6	7.0	6.5	8.0	7.3	6.8	6.4	7.6	7.0	6.6	6.2	5.8																																	
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.2	8.7	8.1	7.5	7.1	8.3	7.8	7.3	6.9	7.9	7.5	7.1	6.7	6.3																																
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.6	9.0	8.4	7.9	7.5	8.6	8.1	7.7	7.3	8.2	7.8	7.4	7.1	6.7																																
1.5m	1.95 m	1.9 m	4.0	9.5	9.0	8.6	8.2	9.3	8.9	8.5	8.1	8.9	8.5	8.2	7.9	8.5	8.2	7.9	7.6	7.2																																
2	2.6	2.5	5.0	9.8	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.1	8.8	8.5	8.2	8.7	8.5	8.2	8.0	7.6																																
2.5	3.21	3.09	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	8.9	9.4	9.1	8.9	8.7	9.0	8.8	8.6	8.4	8.0																																
3	3.85	3.71	10.0	10.2	9.9	9.7	9.5	10.0	9.8	9.5	9.3	9.6	9.4	9.2	9.1	9.2	9.1	8.9	8.8	8.3																																

