

屋内照明器具特性	
品番 (品名)	XLY060HR
光源	LED9999_80_400 x1 400.0 l m
管理番号	K0162646(0)D 1
BZ分類	BZ5

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	5 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	95 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.78	0.6	5.5	4.2	3.4	2.9	5.3	4.2	3.4	2.9	5.0	4.0	3.3	2.8	4.8	3.9	3.2	2.8	2.5			
	中	0.76	0.8	6.4	5.3	4.5	3.9	6.3	5.2	4.4	3.8	5.9	5.0	4.3	3.8	5.6	4.8	4.2	3.7	3.4			
	否	0.72	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.5	6.5	5.6	5.0	4.5	6.2	5.4	4.8	4.4	4.1			
			1.25	7.7	6.7	5.9	5.3	7.5	6.5	5.8	5.2	7.1	6.3	5.6	5.1	6.7	6.0	5.5	5.0	4.7			
下方投影面積		cm ²	1.5	8.1	7.2	6.4	5.8	7.9	7.0	6.3	5.8	7.5	6.7	6.1	5.7	7.1	6.5	6.0	5.5	5.2			
等価発光面積		cm ²	2.0	8.7	7.9	7.2	6.7	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.4	7.6	7.1	6.7	6.3	5.9			
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.1	8.4	7.8	7.4	7.0	8.0	7.5	7.2	6.8	6.4			
	横方向 (A)	縦方向 (B)	3.0	9.3	8.6	8.1	7.7	9.0	8.5	8.0	7.6	8.6	8.2	7.7	7.4	8.3	7.9	7.5	7.2	6.8			
1.5m	1.94 m	1.9 m	4.0	9.6	9.1	8.7	8.3	9.4	8.9	8.5	8.1	9.0	8.6	8.2	7.9	8.6	8.3	8.0	7.7	7.3			
2	2.58	2.5	5.0	9.8	9.4	9.0	8.6	9.6	9.2	8.8	8.5	9.2	8.9	8.6	8.3	8.8	8.5	8.3	8.1	7.7			
2.5	3.22	3.1	7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.3	9.0	9.4	9.2	9.0	8.7	9.1	8.9	8.7	8.5	8.1			
3	3.83	3.69	10.0	10.2	10.0	9.8	9.5	10.0	9.8	9.6	9.4	9.6	9.5	9.3	9.1	9.3	9.1	9.0	8.9	8.4			

