

# 屋内照明器具特性

|         |                   |          |  |
|---------|-------------------|----------|--|
| 品番 (品名) | XND0605BYK        |          |  |
| 光源      | LED2700_85_465 ×1 | 465.0 lm |  |
| 管理番号    | K0176493(0)DB1    |          |  |
| BZ分類    | BZ1               |          |  |

|                  |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|------------------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率             | 101%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|                  | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 下方光束             | 101%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
| 室指数              | 照明率 (X0.01)     |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |
| 保守率              | 良 0.81          | 0.6     | 89   | 84  | 81  | 79  | 89  | 84  | 81  | 79  | 88  | 84  | 81  | 79  | 87  | 83  | 80  | 79  | 78  |     |
|                  | 中 0.77          |         | 0.8  | 94  | 90  | 87  | 85  | 94  | 90  | 87  | 85  | 92  | 89  | 86  | 84  | 91  | 88  | 86  | 84  | 83  |
|                  | 否 0.68          |         | 1.0  | 97  | 93  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 90  | 88  | 94  | 91  | 89  | 87  | 86  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 100  | 96  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 95  | 93  | 91  | 96  | 94  | 92  | 90  | 89  |     |
|                  |                 | 1.5     | 101  | 98  | 96  | 94  | 100 | 98  | 95  | 94  | 99  | 96  | 94  | 93  | 97  | 95  | 94  | 92  | 91  |     |
|                  |                 | 2.0     | 103  | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 101 | 99  | 97  | 96  | 99  | 97  | 96  | 95  | 93  |     |
| 取付高さ             | 器具間隔最大限         |         | 2.5  | 105 | 102 | 101 | 99  | 104 | 102 | 100 | 98  | 102 | 100 | 99  | 97  | 100 | 99  | 97  | 96  | 95  |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0  | 105 | 103 | 102 | 100 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 101 | 99  | 98  | 98  | 96  |
| Hm               | 0.44Hm          | 0.44Hm  | 4.0  | 106 | 105 | 104 | 102 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 100 | 99  | 97  |
|                  |                 |         | 5.0  | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 98  |
|                  |                 |         | 7.0  | 108 | 107 | 106 | 105 | 106 | 106 | 105 | 104 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 98  |
|                  |                 |         | 10.0 | 108 | 107 | 107 | 106 | 107 | 106 | 106 | 105 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 102 | 99  |

