

屋内照明器具特性	
品番 (品名)	S N C X 5 8 2 0 2
光源	LED6200_70_5499 ×1 5499.0 lm
管理番号	K0181799 (0) DR 1
BZ分類	BZ6/1.1/BZ5/3.5/BZ6/4.5/BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		2 6 %	室指数	照明率 (X 0 . 0 1) Z C M																					
下方光束		7 4 %																							
保守率		良 中 否	0 . 6 3	0 . 6	5 1	3 9	3 1	2 6	4 8	3 7	3 0	2 5	4 4	3 4	2 8	2 3	3 9	3 1	2 6	2 2	1 8				
			0 . 6	0 . 8	6 0	4 8	4 0	3 5	5 7	4 6	3 9	3 4	5 1	4 3	3 6	3 1	4 6	3 9	3 4	2 9	2 5				
			0 . 5 6	1 . 0	6 7	5 5	4 7	4 1	6 3	5 3	4 6	4 0	5 7	4 9	4 2	3 8	5 1	4 4	3 9	3 5	3 0				
				1 . 2 5	7 2	6 2	5 4	4 8	6 9	5 9	5 2	4 7	6 2	5 4	4 8	4 4	5 6	5 0	4 5	4 1	3 5				
下方投影面積		cm ²	1 . 5	7 6	6 7	6 0	5 4	7 3	6 4	5 7	5 2	6 6	5 9	5 3	4 9	5 9	5 4	4 9	4 5	3 9					
等価発光面積		cm ²	2 . 0	8 2	7 4	6 7	6 2	7 8	7 1	6 5	6 0	7 1	6 5	6 0	5 6	6 4	5 9	5 5	5 2	4 5					
取付 高さ	器具間隔最大限		2 . 5	8 6	7 9	7 3	6 8	8 2	7 5	7 0	6 5	7 4	6 9	6 5	6 1	6 7	6 3	6 0	5 6	4 9					
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 2	7 7	7 2	8 4	7 9	7 4	7 0	7 7	7 2	6 8	6 5	7 0	6 6	6 3	6 0	5 2					
1 . 5m	2 . 0 2 m	1 . 9 5 m	4 . 0	9 1	8 6	8 2	7 8	8 7	8 3	7 9	7 5	8 0	7 6	7 3	7 0	7 3	7 0	6 7	6 5	5 6					
2	2 . 6 6	2 . 5 6	5 . 0	9 4	8 9	8 6	8 2	9 0	8 6	8 2	7 9	8 2	7 9	7 6	7 3	7 5	7 2	7 0	6 8	5 9					
2 . 5	3 . 3 2	3 . 1 9	7 . 0	9 6	9 3	9 0	8 7	9 2	8 9	8 6	8 4	8 4	8 2	8 0	7 8	7 7	7 5	7 3	7 2	6 3					
3	3 . 9 4	3 . 8	1 0 . 0	9 8	9 5	9 3	9 1	9 4	9 2	9 0	8 8	8 6	8 5	8 3	8 1	7 9	7 8	7 6	7 5	6 6					

