

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | XND0606WBK        |          |
| 光源      | LED4000_85_475 ×1 | 475.0 lm |
| 管理番号    | K0176480(0)DB1    |          |
| BZ分類    | BZ1               |          |

|        |             |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |
|--------|-------------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|
| 器具効率   | 100%        | 天井              | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |     |
|        | 上方光束        |                 | 0%   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0%  |
| 下方光束   | 100%        | 床               | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |     |
| 室指数    | 照明率 (X0.01) |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |
| 保守率    | 良           | 0.81            | 0.6  | 79  | 72  | 67  | 64  | 78  | 72  | 67  | 64  | 77  | 71  | 67  | 64  | 75  | 70  | 66  | 64 | 62  |
|        | 中           | 0.77            | 0.8  | 87  | 80  | 76  | 73  | 86  | 80  | 76  | 73  | 84  | 79  | 75  | 73  | 83  | 78  | 75  | 72 | 71  |
|        | 否           | 0.68            | 1.0  | 91  | 86  | 82  | 79  | 90  | 85  | 81  | 79  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 78 | 76  |
| 下方投影面積 | 等価発光面積      | cm <sup>2</sup> | 1.25 | 95  | 90  | 87  | 84  | 94  | 90  | 86  | 83  | 92  | 88  | 85  | 83  | 90  | 87  | 85  | 82 | 81  |
|        |             |                 | 1.5  | 97  | 93  | 90  | 87  | 96  | 92  | 89  | 87  | 94  | 91  | 88  | 86  | 93  | 90  | 88  | 86 | 84  |
| 取付高さ   | 器具間隔最大限     |                 | 2.5  | 102 | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 99  | 97  | 95  | 93  | 97  | 95  | 94  | 92 | 90  |
|        | 横方向 (A)     | 縦方向 (B)         | 3.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94 | 92  |
| Hm     | 0.73Hm      | 0.73Hm          | 4.0  | 105 | 103 | 101 | 100 | 104 | 102 | 100 | 99  | 101 | 100 | 99  | 97  | 99  | 98  | 97  | 96 | 94  |
|        |             |                 | 5.0  | 106 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 97 | 95  |
|        |             |                 | 7.0  | 107 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 100 | 99  | 97 |     |
|        |             |                 | 10.0 | 107 | 106 | 106 | 105 | 106 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 98 |     |

