

屋内照明器具特性	
品番 (品名)	XAD3 1 0 0 V
光源	LED3500_70_700 ×1 700.0 l m
管理番号	K0166804 (0) DB 1
BZ分類	BZ4 / 0.7 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 7	0 . 6	6 1	5 0	4 3	3 8	6 0	4 9	4 2	3 8	5 8	4 8	4 2	3 7	5 6	4 7	4 2	3 7	3 6				
			0 . 6 3	0 . 8	7 2	6 1	5 4	4 9	7 0	6 1	5 4	4 9	6 8	5 9	5 3	4 9	6 6	5 8	5 3	4 9	4 7				
			0 . 5 6	1 . 0	7 8	6 9	6 2	5 7	7 7	6 8	6 2	5 7	7 4	6 7	6 1	5 7	7 2	6 6	6 1	5 7	5 5				
				1 . 2 5	8 4	7 6	7 0	6 5	8 3	7 5	6 9	6 5	8 0	7 4	6 8	6 4	7 8	7 2	6 8	6 4	6 2				
下方投影面積 等価発光面積		c m ²	1 . 5	8 8	8 1	7 5	7 0	8 7	8 0	7 4	7 0	8 4	7 8	7 3	7 0	8 1	7 6	7 2	6 9	6 7					
			2 . 0	9 3	8 7	8 2	7 8	9 2	8 6	8 2	7 8	8 9	8 4	8 0	7 7	8 6	8 2	7 9	7 6	7 4					
			2 . 5	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 3	9 2	8 8	8 5	8 2	9 0	8 6	8 3	8 1	7 8					
取付 高さ	器具間隔最大限		3 . 0	9 8	9 4	9 0	8 7	9 7	9 3	8 9	8 6	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 2					
	横方向 (A)	縦方向 (B)	4 . 0	1 0 1	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6					
H m	1 . 2 5 H m	1 . 2 5 H m	5 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	8 8					
			7 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 5	9 4	9 1					
			1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 0	9 9	9 8	9 9	9 8	9 7	9 7	9 4					

