

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLG419VGN( JYOUJI )          |
| 光源       | LED5000_85_1940 ×1 1940.0 lm |
| 管理番号     | K0176622 ( 0 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率     |           | 100 %           | 反射率  | 天井            | 80 % |     |    |     | 70 % |    |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |      |  |
|----------|-----------|-----------------|------|---------------|------|-----|----|-----|------|----|----|-----|------|----|----|----|------|----|----|----|-----|------|--|
|          |           |                 |      | 壁             | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |      |  |
| 上方光束     |           | 0 %             |      | 床             | 10 % |     |    |     | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |      |  |
| 下方光束     |           | 100 %           | 室指数  | 照明率 ( X0.01 ) |      |     |    |     |      |    |    |     |      |    |    |    |      |    |    |    |     | Z CM |  |
| 保守率      |           | 良<br>中<br>否     | 0.81 | 0.6           | 56   | 44  | 36 | 30  | 55   | 43 | 36 | 30  | 52   | 42 | 35 | 30 | 50   | 41 | 35 | 30 | 28  |      |  |
|          |           |                 | 0.77 | 0.8           | 66   | 54  | 46 | 41  | 65   | 54 | 46 | 40  | 62   | 52 | 45 | 40 | 59   | 51 | 45 | 40 | 38  |      |  |
|          |           |                 | 0.68 | 1.0           | 73   | 62  | 54 | 48  | 71   | 61 | 53 | 48  | 68   | 59 | 53 | 47 | 65   | 58 | 52 | 47 | 45  |      |  |
|          |           |                 |      | 1.25          | 79   | 69  | 61 | 55  | 77   | 68 | 61 | 55  | 74   | 66 | 60 | 55 | 71   | 64 | 59 | 54 | 52  |      |  |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5  | 83            | 74   | 67  | 61 | 81  | 73   | 66 | 61 | 78  | 71   | 65 | 60 | 75 | 69   | 64 | 60 | 57 |     |      |  |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0  | 89            | 81   | 75  | 70 | 87  | 80   | 74 | 69 | 84  | 78   | 73 | 68 | 81 | 76   | 71 | 68 | 65 |     |      |  |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5  | 92            | 86   | 80  | 76 | 91  | 85   | 79 | 75 | 87  | 82   | 78 | 74 | 85 | 80   | 76 | 73 | 70 |     |      |  |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0  | 95            | 89   | 84  | 80 | 93  | 88   | 83 | 79 | 90  | 86   | 82 | 78 | 87 | 84   | 80 | 77 | 74 |     |      |  |
| 1.5m     | 1.96 m    | 2.12 m          | 4.0  | 98            | 94   | 90  | 86 | 97  | 92   | 89 | 85 | 94  | 90   | 87 | 84 | 91 | 88   | 85 | 83 | 80 |     |      |  |
| 2        | 2.59      | 2.67            | 5.0  | 100           | 96   | 93  | 90 | 99  | 95   | 92 | 89 | 96  | 93   | 90 | 88 | 93 | 91   | 88 | 86 | 83 |     |      |  |
| 2.5      | 3.22      | 3.23            | 7.0  | 102           | 100  | 97  | 95 | 101 | 98   | 96 | 94 | 98  | 96   | 94 | 92 | 96 | 94   | 92 | 90 | 88 |     |      |  |
| 3        | 3.85      | 3.81            | 10.0 | 104           | 102  | 100 | 98 | 103 | 101  | 99 | 98 | 100 | 99   | 97 | 96 | 98 | 96   | 95 | 94 | 91 |     |      |  |

