

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XDL439KGN( J Y O U J I )     |
| 光源       | LED5000_85_3140 ×1 3140.0 lm |
| 管理番号     | K0194634 ( 0 ) D 1           |
| B Z 分類   | BZ5 / 1.8 / BZ4              |

| 器具効率     |           | 100 %           | 反射率    | 天井   | 80 %              |     |    |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|-----------------|--------|------|-------------------|-----|----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|
|          |           |                 |        | 壁    | 70                | 50  | 30 | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                 |        | 床    | 10 %              |     |    |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                 |        | 室指数  | 照明率 ( X0.01 ) ZCM |     |    |     |      |     |    |     |      |    |    |    |      |    |    |    |     |
| 保守率      |           | 良<br>中<br>否     | 0.81   | 0.6  | 57                | 45  | 37 | 32  | 56   | 44  | 37 | 32  | 53   | 43 | 36 | 32 | 51   | 42 | 36 | 31 | 29  |
|          |           |                 | 0.77   | 0.8  | 67                | 56  | 48 | 42  | 66   | 55  | 48 | 42  | 63   | 54 | 47 | 42 | 60   | 52 | 46 | 42 | 40  |
|          |           |                 | 0.68   | 1.0  | 74                | 63  | 56 | 50  | 72   | 62  | 55 | 50  | 69   | 61 | 54 | 49 | 67   | 59 | 53 | 49 | 47  |
|          |           |                 |        | 1.25 | 80                | 70  | 63 | 57  | 78   | 69  | 63 | 57  | 75   | 67 | 62 | 57 | 72   | 66 | 61 | 56 | 54  |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5    | 84   | 75                | 69  | 63 | 82  | 74   | 68  | 63 | 79  | 72   | 67 | 62 | 76 | 70   | 66 | 62 | 59 |     |
|          |           |                 | 等価発光面積 |      | cm <sup>2</sup>   | 2.0 | 90 | 82  | 77   | 72  | 88 | 81  | 76   | 71 | 85 | 79 | 74   | 70 | 82 | 77 | 73  |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5    | 93   | 87                | 82  | 77 | 92  | 86   | 81  | 77 | 89  | 84   | 80 | 76 | 86 | 82   | 78 | 75 | 72 |     |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0    | 96   | 90                | 86  | 82 | 94  | 89   | 85  | 81 | 91  | 87   | 83 | 80 | 88 | 85   | 82 | 79 | 76 |     |
| 1.5m     | 1.93 m    | 2.11 m          | 4.0    | 99   | 95                | 91  | 88 | 97  | 93   | 90  | 87 | 94  | 91   | 88 | 85 | 92 | 89   | 86 | 84 | 81 |     |
| 2        | 2.55      | 2.65            | 5.0    | 101  | 97                | 94  | 91 | 99  | 96   | 93  | 90 | 96  | 94   | 91 | 89 | 94 | 91   | 89 | 87 | 85 |     |
| 2.5      | 3.17      | 3.22            | 7.0    | 103  | 100               | 98  | 96 | 101 | 99   | 97  | 95 | 99  | 97   | 95 | 93 | 96 | 94   | 93 | 91 | 89 |     |
| 3        | 3.78      | 3.79            | 10.0   | 104  | 103               | 101 | 99 | 103 | 101  | 100 | 98 | 100 | 99   | 98 | 96 | 98 | 97   | 96 | 95 | 92 |     |

