

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | XND0635SW         |          |
| 光源      | LED4000_85_555 ×1 | 555.0 lm |
| 管理番号    | K0176633(0)DB1    |          |
| BZ分類    | BZ1               |          |

|                  |                 |         |             |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|------------------|-----------------|---------|-------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率             | 101%            | 天井      | 80%         |      |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|                  | 上方光束            |         | 0%          | 70   | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
| 下方光束             | 101%            | 床       | 10%         |      |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 室指数              |                 |         | 照明率 (X0.01) |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率              | 良               | 0.81    | 0.6         | 89   | 84  | 81  | 79  | 89  | 84  | 81  | 79  | 88  | 83  | 81  | 79  | 86  | 83  | 80  | 78  | 78 |
|                  | 中               | 0.77    | 0.8         | 94   | 90  | 87  | 85  | 94  | 90  | 87  | 85  | 92  | 89  | 86  | 84  | 91  | 88  | 86  | 84  | 83 |
|                  | 否               | 0.68    | 1.0         | 97   | 93  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 90  | 88  | 94  | 91  | 89  | 87  | 86 |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 1.00        | 96   | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 95  | 93  | 91  | 96  | 94  | 92  | 90  | 89  |    |
|                  |                 | 1.5     | 1.01        | 98   | 96  | 94  | 101 | 98  | 95  | 94  | 99  | 97  | 95  | 93  | 97  | 95  | 94  | 92  | 91  |    |
|                  |                 | 2.0     | 1.03        | 101  | 99  | 97  | 103 | 100 | 98  | 97  | 101 | 99  | 97  | 96  | 99  | 97  | 96  | 95  | 93  |    |
| 取付高さ             | 器具間隔最大限         |         | 2.5         | 1.05 | 103 | 101 | 99  | 104 | 102 | 100 | 99  | 102 | 100 | 99  | 98  | 100 | 99  | 98  | 97  | 95 |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0         | 1.05 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 103 | 101 | 100 | 99  | 101 | 100 | 99  | 98  | 96 |
| Hm               | 0.44Hm          | 0.44Hm  | 4.0         | 1.06 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 101 | 100 | 99  | 97 |
|                  |                 |         | 5.0         | 1.07 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 104 | 103 | 102 | 102 | 102 | 101 | 101 | 100 | 98 |
|                  |                 |         | 7.0         | 1.08 | 107 | 106 | 105 | 107 | 106 | 105 | 104 | 105 | 104 | 103 | 103 | 103 | 102 | 102 | 101 | 99 |
|                  |                 |         | 10.0        | 1.08 | 108 | 107 | 106 | 107 | 107 | 106 | 105 | 105 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 99 |

