

屋内照明器具特性	
品番 (品名)	XLG429VGN(JYOUJI)
光源	LED5000_85_2420 ×1 2420.0 lm
管理番号	K0176622 (0) DR 1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 8 1	0 . 6	5 6	4 4	3 6	3 0	5 5	4 3	3 6	3 0	5 2	4 2	3 5	3 0	5 0	4 1	3 5	3 0	2 8	
			0 . 7 7	0 . 8	6 6	5 4	4 6	4 1	6 5	5 4	4 6	4 0	6 2	5 2	4 5	4 0	5 9	5 1	4 5	4 0	3 8	
				1 . 0	7 3	6 2	5 4	4 8	7 1	6 1	5 3	4 8	6 8	5 9	5 3	4 7	6 5	5 8	5 2	4 7	4 5	
			0 . 6 8	1 . 2 5	7 9	6 9	6 1	5 5	7 7	6 8	6 1	5 5	7 4	6 6	6 0	5 5	7 1	6 4	5 9	5 4	5 2	
下方投影面積		cm ²		1 . 5	8 3	7 4	6 7	6 1	8 1	7 3	6 6	6 1	7 8	7 1	6 5	6 0	7 5	6 9	6 4	6 0	5 7	
等価発光面積		cm ²		2 . 0	8 9	8 1	7 5	7 0	8 7	8 0	7 4	6 9	8 4	7 8	7 3	6 8	8 1	7 6	7 1	6 8	6 5	
取付 高さ	器具間隔最大限			2 . 5	9 2	8 6	8 0	7 6	9 1	8 5	7 9	7 5	8 7	8 2	7 8	7 4	8 5	8 0	7 6	7 3	7 0	
	横方向 (A)	縦方向 (B)		3 . 0	9 5	8 9	8 4	8 0	9 3	8 8	8 3	7 9	9 0	8 6	8 2	7 8	8 7	8 4	8 0	7 7	7 4	
1 . 5m	1 . 9 6 m	2 . 1 2 m		4 . 0	9 8	9 4	9 0	8 6	9 7	9 2	8 9	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 0	
2	2 . 5 9	2 . 6 7		5 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 8	8 6	8 3	
2 . 5	3 . 2 2	3 . 2 3		7 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 0	8 8	
3	3 . 8 5	3 . 8 1		1 0 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 6	9 5	9 4	9 1	

