

屋内照明器具特性	
品番 (品名)	XDL449VGN(J Y O U J I)
光源	LED5000_85_3880 ×1 3880.0 l m
管理番号	K0194643 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 8 1	0 . 6	5 6	4 4	3 6	3 1	5 5	4 3	3 6	3 1	5 3	4 2	3 5	3 0	5 0	4 1	3 5	3 0	2 8				
			0 . 7 7	0 . 8	6 6	5 5	4 7	4 1	6 5	5 4	4 6	4 1	6 2	5 2	4 6	4 0	5 9	5 1	4 5	4 0	3 8				
			1 . 0	7 3	6 2	5 4	4 8	7 1	6 1	5 4	4 8	6 8	5 9	5 3	4 8	6 6	5 8	5 2	4 7	4 5					
			0 . 6 8	1 . 2 5	7 9	6 9	6 1	5 6	7 7	6 8	6 1	5 5	7 4	6 6	6 0	5 5	7 1	6 4	5 9	5 4	5 2				
下方投影面積 等価発光面積		c m ²	1 . 5	8 3	7 4	6 7	6 1	8 1	7 3	6 6	6 1	7 8	7 1	6 5	6 0	7 5	6 9	6 4	6 0	5 7					
			2 . 0	8 9	8 1	7 5	7 0	8 7	8 0	7 4	6 9	8 4	7 8	7 3	6 9	8 1	7 6	7 2	6 8	6 5					
取付 高さ	器具間隔最大限		2 . 5	9 2	8 6	8 0	7 6	9 1	8 5	8 0	7 5	8 8	8 3	7 8	7 4	8 5	8 0	7 7	7 3	7 1					
	横方向 (A)	縦方向 (B)	3 . 0	9 5	8 9	8 4	8 0	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 8	8 8	8 4	8 0	7 7	7 5					
1 . 5 m	1 . 9 6 m	2 . 1 1 m	4 . 0	9 8	9 4	9 0	8 6	9 7	9 3	8 9	8 5	9 4	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 0					
2	2 . 5 9	2 . 6 4	5 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 9	8 6	8 4					
2 . 5	3 . 2 2	3 . 2	7 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 8					
3	3 . 8 5	3 . 7 8	1 0 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 7	9 5	9 4	9 1					

