

屋内照明器具特性	
品番 (品名)	X F L 3 2 3 G A
光源	LDL40S. N/ 14/ 26 (2 6 0 0 A) ×2 2 6 0 0 . 0 1 m
管理番号	K 0 1 2 6 7 6 4 (1) D R 1
B Z 分類	B Z 4

器具効率		8 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		8 1 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 8 1	0 . 6	4 8	3 8	3 2	2 8	4 7	3 8	3 2	2 8	4 5	3 7	3 1	2 8	4 3	3 6	3 1	2 8	2 6
			0 . 7 7	0 . 8	5 6	4 7	4 1	3 7	5 5	4 7	4 1	3 7	5 3	4 6	4 0	3 6	5 1	4 5	4 0	3 6	3 5
			0 . 6 8	1 . 0	6 1	5 3	4 7	4 3	6 0	5 3	4 7	4 3	5 8	5 1	4 7	4 3	5 6	5 0	4 6	4 2	4 1
				1 . 2 5	6 6	5 9	5 3	4 9	6 5	5 8	5 3	4 9	6 3	5 7	5 2	4 9	6 0	5 6	5 2	4 8	4 7
下方投影面積		cm ²	1 . 5	6 9	6 3	5 8	5 4	6 8	6 2	5 7	5 3	6 6	6 1	5 6	5 3	6 4	5 9	5 6	5 3	5 1	
等価発光面積		cm ²	2 . 0	7 4	6 8	6 4	6 0	7 2	6 7	6 3	6 0	7 0	6 6	6 2	5 9	6 8	6 4	6 1	5 9	5 7	
取付 高さ	器具間隔最大限		2 . 5	7 6	7 2	6 8	6 5	7 5	7 1	6 7	6 4	7 3	6 9	6 6	6 3	7 1	6 8	6 5	6 3	6 1	
	横方向 (A) 縦方向 (B)		3 . 0	7 8	7 4	7 1	6 8	7 7	7 3	7 0	6 7	7 5	7 2	6 9	6 6	7 3	7 0	6 8	6 6	6 4	
1 . 5m	2 . 0 9 m	2 . 1 5 m	4 . 0	8 1	7 7	7 5	7 2	7 9	7 6	7 4	7 2	7 7	7 5	7 3	7 1	7 5	7 3	7 1	6 9	6 7	
2	2 . 7 8	2 . 7 1	5 . 0	8 2	7 9	7 7	7 5	8 1	7 8	7 6	7 4	7 9	7 7	7 5	7 3	7 7	7 5	7 3	7 2	7 0	
2 . 5	3 . 4 6	3 . 3	7 . 0	8 3	8 2	8 0	7 8	8 2	8 1	7 9	7 7	8 0	7 9	7 7	7 6	7 8	7 7	7 6	7 5	7 3	
3	4 . 1 4	3 . 9	1 0 . 0	8 5	8 3	8 2	8 1	8 4	8 2	8 1	8 0	8 2	8 1	8 0	7 9	8 0	7 9	7 8	7 7	7 5	

