

# 屋内照明器具特性

品番 (品名)	XDL451AGN( J YOUJI )																
光源	LED5000_85_5200 x1 5200.0 lm																
管理番号	K0194617(0)D 1																
BZ分類	BZ5																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	4 %	室指数	照明率 ( X0.01 )																	ZCM	
下方光束	96 %																				
保守率	良 中 否	0.83	0.6	5.6	4.3	3.5	3.0	5.4	4.3	3.5	3.0	5.1	4.1	3.4	2.9	4.9	4.0	3.4	2.9	2.7	
		0.81	0.8	6.5	5.4	4.6	4.0	6.4	5.3	4.5	4.0	6.0	5.1	4.4	3.9	5.7	4.9	4.3	3.8	3.6	
		0.77	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.7	6.6	5.8	5.1	4.6	6.3	5.6	5.0	4.5	4.3	
			1.25	7.8	6.8	6.0	5.4	7.6	6.6	5.9	5.4	7.2	6.4	5.8	5.3	6.9	6.2	5.6	5.2	4.9	
下方投影面積	c m <sup>2</sup>	1.5	8.2	7.3	6.5	6.0	8.0	7.1	6.5	5.9	7.6	6.9	6.3	5.8	7.2	6.6	6.1	5.7	5.4		
		2.0	8.7	7.9	7.3	6.8	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.6	7.8	7.3	6.8	6.5	6.1		
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.8	7.3	8.9	8.3	7.7	7.3	8.5	8.0	7.5	7.1	8.1	7.7	7.3	7.0	6.6	
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.8	9.1	8.6	8.1	7.7	8.8	8.3	7.9	7.5	8.4	8.0	7.7	7.4	7.0	
1.5m	1.96 m	2.1 m	4.0	9.7	9.2	8.7	8.4	9.5	9.0	8.6	8.3	9.1	8.7	8.4	8.1	8.7	8.4	8.1	7.9	7.5	
2	2.58	2.64	5.0	9.9	9.4	9.1	8.7	9.7	9.3	8.9	8.6	9.3	9.0	8.7	8.4	9.0	8.7	8.5	8.2	7.9	
2.5	3.21	3.19	7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.4	9.1	9.5	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.3	
3	3.84	3.76	10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.6	9.4	9.2	9.4	9.3	9.1	9.0	8.6	

