

屋内照明器具特性	
品番 (品名)	XL X430NEWP
光源	LED4000_85_3050 ×1 3050.0 lm
管理番号	K0135074 (*) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		4 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		96 %																							
保守率		良 中 否	0.83	0.6	56	44	36	30	54	43	36	30	52	42	35	30	49	40	34	30	27				
			0.81	0.8	66	54	46	41	64	53	46	40	61	51	45	40	58	50	44	39	37				
			0.77	1.0	72	61	54	48	70	60	53	47	67	58	52	47	64	56	51	46	43				
				1.25	78	68	61	55	76	67	60	55	72	65	59	54	69	62	57	53	50				
下方投影面積		cm ²	1.5	82	73	66	60	80	72	65	60	76	69	64	59	73	67	62	58	55					
等価発光面積		cm ²	2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62					
取付 高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	73	85	80	76	72	82	77	74	70	67					
	横方向 (A) 縦方向 (B)		3.0	94	88	83	78	92	86	82	78	88	83	79	76	84	81	77	74	71					
1.5m	1.94 m	2.1 m	4.0	97	92	88	84	95	90	87	83	91	87	84	81	88	85	82	79	76					
2	2.56	2.64	5.0	99	95	91	88	97	93	90	87	93	90	87	85	90	87	85	83	79					
2.5	3.19	3.21	7.0	101	98	95	93	99	96	94	91	96	93	91	89	92	90	88	87	83					
3	3.8	3.79	10.0	103	101	98	96	101	99	97	95	97	96	94	93	94	93	91	90	86					

