

# 屋内照明器具特性

品番 (品名)	XND1007SW									
光源	LED4000_85_960 x1					960.0 lm				
管理番号	K0176491(0)DB1									
BZ分類	BZ1									

器具効率	100%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	100%																																																						
保守率	良 中 否	0.81	0.6	74	66	60	57	73	65	60	57	71	64	60	56	70	64	59	56	55																																			
		0.77	0.8	83	76	71	67	82	75	71	67	80	74	70	67	79	74	70	67	65																																			
			1.0	89	82	78	74	88	82	78	74	86	81	77	74	84	80	76	74	72																																			
		0.68	1.25	93	87	83	80	92	87	83	80	90	86	82	79	88	84	81	79	77																																			
下方投影面積	c m <sup>2</sup>	1.5	96	91	87	84	94	90	87	84	92	89	86	83	90	87	85	82	81																																				
		2.0	99	95	92	89	98	94	91	89	96	93	90	88	94	91	89	87	85																																				
取付高さ	器具間隔最大限		2.5	101	98	95	93	100	97	94	92	98	95	93	91	96	94	92	90	88																																			
	横方向 (A)	縦方向 (B)	3.0	102	99	97	95	101	99	96	94	99	97	95	93	97	95	94	92	90																																			
H m	1.17H m	1.17H m	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92																																			
			5.0	105	103	101	100	104	102	101	99	101	100	99	98	99	98	97	96	94																																			
			7.0	106	105	103	102	105	104	102	101	102	101	101	100	100	100	99	98	96																																			
			10.0	107	106	105	104	105	105	104	103	103	103	102	101	101	101	100	99	97																																			

