

屋内照明器具特性

品番 (品名)	XND1008 WWK		
光源	LED4000_85_1020 ×1	1020.0 lm	
管理番号	K0176484 (0) DB 1		
BZ分類	BZ1		

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.81	0.6	77	70	65	61	76	69	64	61	75	68	64	61	73	68	64	61	60	
	中 0.77		0.8	85	78	74	70	84	78	73	70	82	77	73	70	81	76	72	70	68
	否 0.68		1.0	90	84	80	76	89	83	79	76	87	82	79	76	85	81	78	75	74
下方投影面積	cm ²	1.25	94	89	85	82	93	88	84	81	91	87	84	81	89	86	83	80	79	
		1.5	97	92	88	85	96	91	88	85	93	90	87	84	92	88	86	84	82	
等価発光面積	cm ²	2.0	100	96	93	90	99	95	92	90	97	94	91	89	95	92	90	88	86	
		2.5	102	99	96	94	101	98	95	93	98	96	94	92	96	94	93	91	89	
取付高さ	器具間隔最大限		3.0	103	100	98	96	102	99	97	95	100	98	96	94	98	96	94	91	
	横方向 (A)	縦方向 (B)	4.0	105	102	101	99	103	101	100	98	101	100	98	97	99	98	97	96	93
Hm	0.74Hm	0.74Hm	5.0	105	104	102	101	104	103	101	100	102	101	100	98	100	99	98	97	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96
			10.0	107	106	105	105	106	105	104	104	104	103	103	102	102	101	101	100	97

